

# TIUNNE PLUS 200 2800LM 840 15D WHITE IP65/IP20 REFLECTOR GS 28W

---

DETAILED CARD



# TIUNNE PLUS 200 2800LM 840 15D WHITE IP65/IP20 REFLECTOR GS 28W

DETAILED CARD

## TECHNICAL PARAMETERS

---

<b>Index:</b>	913488
<b>Ingress protection:</b>	IP65/IP20
<b>Rated power of the luminaire [W]*:</b>	28
<b>Luminous flux [lm]*:</b>	2800
<b>Colour temperature [K]:</b>	4000
<b>Color rendering index (Ra) &gt;:</b>	80
<b>Energy efficiency class:</b>	E
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	white
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

---

Tiunne Plus is a decorative downlight luminaire for installation in suspended ceilings. It is energy-efficient and durable thanks to the COB LED light source used. It has a classic circular shape that blends in with any type of space. It is available in several versions with different light distribution angles and four reflector colours.

The lamp housing designed in aluminium ensures optimum working conditions for the LEDs, and the aluminium reflector guarantees high luminous efficiency and low glare - features that distinguish the best LED downlight luminaires. The luminaire is suitable for installation in plasterboard and modular ceilings. Colour temperature 3000K, 4000K; CRI>80, CRI>90.

## APPLICATION

---

The luminaire is designed for indoor use as general lighting. It is ideal for walkways, entrance areas, shop windows and fitting rooms in commercial premises.

## DETAILS

---

LED lifespan: L70F50 >60 000h; L80F10 >60 000h; L90F10 57 000h


# TIUNNE PLUS 200 2800LM 840 15D WHITE IP65/IP20 REFLECTOR GS 28W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	913488	<b>Optics:</b>	reflector GS
<b>EAN:</b>	5905963913488	<b>Material of the body:</b>	aluminium
<b>Light source:</b>	COB	<b>Colour of the body:</b>	white
<b>Rated power of the luminaire [W]:</b>	28	<b>Ring material:</b>	aluminium
<b>Luminous flux [lm]:</b>	2800	<b>Ring colour:</b>	white
<b>Remarks:</b>	GS - glossy silver	<b>Dimensions (H/W/T/S) [mm]:</b>	ø215/110
<b>Luminous efficacy [lm/W]:</b>	100	<b>Mounting dimensions [mm]:</b>	200
<b>Energy efficiency class:</b>	E	<b>Ingress protection:</b>	IP65/IP20
<b>Electrical protection class:</b>	II	<b>Impact resistance:</b>	IK08
<b>Colour temperature [K]:</b>	4000	<b>Mounting version:</b>	recessed
<b>Color rendering index (Ra) &gt;:</b>	80	<b>Working temperature [°C]:</b>	35
<b>SDCM:</b>	3	<b>Net weight [kg]:</b>	0.550
<b>Beam angle [°]:</b>	15	<b>Category type:</b>	downlights
<b>Surge protection [kV]:</b>	1	<b>Warranty [years]:</b>	5
<b>Diffuser material:</b>	PC	<b>CE certificate:</b>	<a href="#">18/2026</a>
<b>Diffuser type:</b>	transparent	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Optics material:</b>	aluminium	<b>Plik LDT:</b>	<a href="#">Download</a>

## LIGHT CURVES



# TIUNNE PLUS 200 2800LM 840 15D WHITE IP65/IP20 REFLECTOR GS 28W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
416835	Masking ring 198/257 Tiunne Plus 200 RAL9016
416859	Masking ring 198/257 Square Tiunne Plus 200 RAL9016

Card creation date: 23 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 18/2026



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl