

# ASTRA LED ALU 6950LM 830 AR3 IP66 II CL. WIRE 0,7M WTYK/GN SP10KV (53W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	580482
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK08
<b>Rated power of the luminaire [W]*:</b>	53
<b>Luminous flux [lm]*:</b>	6950
<b>Colour temperature [K]:</b>	3000
<b>Colour rendering index:</b>	> 80
<b>Electrical protection class:</b>	II
<b>Optics:</b>	AR3
<b>Colour of the body:</b>	grey

## CHARACTERISTICS

LED road luminaire with high luminous efficacy (up to 151 lm/W) and energy-efficient integrated LED module. Self-cleaning body and handle made of powder-coated aluminium. The luminaire uses directional lens matrices (made of polycarbonate PC). The luminaire is characterised by a high degree of protection IP66 and mechanical impact resistance IK08 (vandal resistant). The integrated bracket, adjustable in increments of 5 degrees, allows adjustment from: -5° to +15° (top, on pole); -15° to +5° (side, on boom). Constructed as standard with 0.7m of H07RN-F cable with IP66 quick-connector. Additional options: painting in any RAL colour; RCR sensor controlled by remote control. Certifications: CE, RoHS, ENEC.

## APPLICATION

Road luminaire for use in open areas, for lighting: streets, local roads, cycle paths, alleys, pavements, car parks and squares.

# ASTRA LED ALU 6950LM 830 AR3 IP66 II CL. WIRE 0,7M WTYK/GN SP10KV (53W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	580482	Colour of the body:	grey
EAN:	5905963580482	Dimensions (H/W/T/S) [mm]:	640/233/113
ETIM class:	EC000062	Mounting dimensions [mm]:	ø60
Category type:	street lighting	Impact resistance:	IK08
Light source:	LED module	Ingress protection:	IP66
Rated power of the luminaire [W]:	53	Mounting version:	Top, on pole / Side, on boom
Supply voltage [V]:	220 - 240	Beam angle adjustment [°]:	-5 to +15 (peak); -15 to +5 (side)
Frequency [Hz]:	50 - 60	Lateral surface (SCx) [m2]:	0.018
Luminous flux [lm]:	6950	Working temperature [°C]:	from -20 to +35
Luminous efficacy [lm/W]:	131	LED lifespan L90B10 [h]:	34000
Energy efficiency class:	D	Wire type:	H07RN-F
Electrical protection class:	II	ULOR:	0%
Colour temperature [K]:	3000	LED lifespan L70B50 [h]:	120000
Colour rendering index:	> 80	LED lifespan L80B20 [h]:	75000
SDCM:	≤ 5	Control:	ON/OFF
Power factor:	0.97	Cable length [m]:	0.70
Surge protection [kV]:	10	Net weight [kg]:	2.950
Diffuser type:	matrix led	Warranty [years]:	5
Optics material:	PC	CE certificate:	<a href="#">467/2023</a>
Optics:	AR3	ENEC Certificate:	<a href="#">0324/ENEC/23</a>
Material of the body:	powder coated aluminium	Manual:	<a href="#">Download PDF</a>

## LIGHT CURVES



# ASTRA LED ALU 6950LM 830 AR3 IP66 II CL. WIRE 0,7M WTYK/GN SP10KV (53W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)
UL00229	mounting grip 78 mm



wall holder (galvanized) (314049)



wall holder (grey) (314056)



mounting grip 78 mm (UL00229)

Card creation date: 12 September 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 467/2023