

LINEA S LED 1176MM IP40 11P 2C

DETAILED CARD



TECHNICAL PARAMETERS

Index:	983825
Ingress protection:	IP40
Material of the body:	Steel
Colour of the body:	RAL9010
Mounting version:	surface, suspended
Dimensions (H/W/T/S) [mm]:	1176/53/28
Through wiring:	LS2,5
Impact resistance:	IK03

CHARACTERISTICS

LINEA S LED is a surface-mounted and suspended light-line system, representing a new generation of luminaires dedicated to LED technology. The innovative connection system and loop-through cabling enables the rapid assembly of luminaires into a light line and allows flexible replacement of light modules to meet current needs. The design used allows for easy assembly and power connection. The steel body, designed from the ground up, ensures the luminaire's strength and robustness, while the narrow side profile allows installation in hard-to-reach areas. Diodes from a renowned manufacturer and new LED modules contribute to the very high luminous efficiency.

APPLICATION

Versatile led lamp designed for indoor use, especially recommended for lighting large-scale commercial, manufacturing and warehouse facilities. The lamp for use in both new applications and replacements of traditional T8 and T5 fixtures with energy-efficient LED solutions.

LINEA S LED 1176MM IP40 11P 2C

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	983825	Number on the palette [pcs]:	104
EAN:	5905963983825	Net weight [kg]:	1.120
Material of the body:	Steel	Electrical protection class:	I
Colour of the body:	RAL9010	Mounting dimensions [mm]:	1150
Dimensions (H/W/T/S) [mm]:	1176/53/28	Impact resistance:	IK03
Ingress protection:	IP40	Warranty [years]:	5
Mounting version:	surface, suspended	Additional accessories:	end cap IP40, end cap IP44, zawiesie, uchwyty montażowy natynkowy, maskownice PVC, maskownice metalowe, zestawy zasilające
Working temperature [°C]:	from -25 to +35	Manual:	Download PDF
Wire type:	5x2,5 + 6x1,5	Mark D:	yes
Through wiring:	LS2,5	Environmental Product Declaration (EPD):	869/2025
Category type:	quick assembly lines	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Remarks:	Number of connectors: 2		

LINEA S LED 1176MM IP40 11P 2C

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
980039	LINEA S LED masking 1764mm
980060	LINEA S LED – end cap IP40 push-in
980077	LINEA S LED hang 3m
980084	LINEA S LED power set 5P
980930	LINEA S LED PVC bezel 1176mm
981159	LINEA S LED - PVC grille 1764mm
981388	LINEA S LED power set 11P
981166	LINEA S LED – end cap IP40 for screws
980947	LINEA S LED metal grille 1176mm
980985	LINEA S LED metal grille 588mm
981173	LINEA S LED hang 1.5m
980954	Linea S LED surface mount bracket
981418	LINEA S LED pendant sm 1.5
981425	LINEA S LED chain pendant
980978	Linea S LED power set 7P
980961	LINEA S LED pendant sm 3m
981401	LINEA S LED IP40 connection bezel

LINEA S LED 1176MM IP40 11P 2C

DETAILED CARD



LINEA S LED masking
1764mm (980039)



LINEA S LED - end cap IP40 push-in
(980060)



LINEA S LED power set 5P (980084)



LINEA S LED PVC bezel
1176mm (980930)



LINEA S LED - PVC grille
1764mm (981159)



LINEA S LED power set 11P (981388)



LINEA S LED metal grille
1176mm (980947)



LINEA S LED metal grille
588mm (980985)



LINEA S LED hang 1.5m (981173)



Linea S LED surface mount
bracket (980954)



LINEA S LED chain pendant (981425)



Linea S LED power set 7P (980978)

Card creation date: 09 February 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: