

# SOLANTO Z 1200MM 4300LM TUNABLE WHITE 2700-6500K IP20 I KL. OPAL CZARNY 68W

DETAILED CARD



## TECHNICAL PARAMETERS

|  |             |
|--|-------------|
| Light source:                                | LED module  |
| Rated power [W] - range:                     | 68          |
| Colour temperature [K] - range:              | 2700 - 6500 |
| Luminous flux of the luminaire [lm] - range: | 4300        |
| Ingress protection:                          | IP20        |
| Electrical protection class:                 | I           |
| Diffuser material:                           | PMMA        |
| Diffuser type:                               | OPAL        |
| Colour of the body:                          | black       |

## CHARACTERISTICS

Suspended-mounted ring-shaped LED luminaire, allowing for an attractive arrangement of representative interiors. The luminaire is made of steel powder-coated in black to fit the character of the interior. The milky diffuser made with thermoforming method emphasises the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

## APPLICATION

SOLANTO is an extremely glamorous pendant or surface mounted luminaire, dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can be also used in apartments and apartments, perfectly fitting into stylish surroundings.

# SOLANTO Z 1200MM 4300LM TUNABLE WHITE 2700-6500K IP20 I KL. OPAL CZARNY 68W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|  |             |                            |                              |
|--|-------------|----------------------------|------------------------------|
| Index:                                       | 467370      | Diffuser material:         | PMMA                         |
| Light source:                                | LED module  | Diffuser type:             | OPAL                         |
| Rated power [W] - range:                     | 68          | Material of the body:      | Steel                        |
| Luminous flux of the luminaire [lm] - range: | 4300        | Colour of the body:        | black                        |
| Supply voltage [V]:                          | 220 - 240   | Ring colour:               | black                        |
| Frequency [Hz]:                              | 50 - 60     | Dimensions (H/W/T/S) [mm]: | ø1200/32                     |
| Luminous efficacy [lm/W]:                    | 63          | Mounting dimensions [mm]:  | 340/340                      |
| Energy efficiency class:                     | G           | Ingress protection:        | IP20                         |
| Electrical protection class:                 | I           | Mounting version:          | suspended                    |
| Colour temperature [K] - range:              | 2700 - 6500 | Cable length [m]:          | 1.35                         |
| Colour rendering index:                      | 80          | Net weight [kg]:           | 5.800                        |
| SDCM:  | ≤ 3         | Warranty [years]:          | 5                            |
| LED lifespan L70B50 [h]:                     | 112000      | CE certificate:            | <a href="#">218/2023</a>     |
| LED lifespan L80B20 [h]:                     | 70 000      | Manual:                    | <a href="#">Download PDF</a> |
| LED lifespan L90B10 [h]:                     | 34000       | Plik LDT:                  | <a href="#">Download</a>     |

Card creation date:19 May 2025  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 218/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)