

SOLANTO Z 1200MM 4300LM TUNABLE WHITE 2700-6500K IP20 I KL. OPAL CZARNY 68W

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	moduł LED
Rated power [W] - range:	30-53
Colour temperature [K]:	3000; 4000
Colour temperature [K] - range:	2700 - 6500
Luminous flux of the luminaire [lm] - range:	1890 - 6100
Ingress protection:	IP20
Electrical protection class:	I
Diffuser material:	PMMA; PS
Diffuser type:	OPAL
Colour of the body:	biały; czarny

CHARACTERISTICS

Suspended or surface-mounted ring-shaped LED luminaire, allowing for an attractive arrangement of representative interiors. The luminaire is made of steel powder coated in white, black or other color to fit the character of the interior. The milky diffuser made with thermoforming method emphasises the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings increasing the versatility and functionality of the luminaire, while reducing the number of indexes to the necessary minimum.

APPLICATION

SOLANTO is an extremely glamorous pendant or surface mounted luminaire, dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can be also used in apartments and apartments, perfectly fitting into stylish surroundings.

SOLANTO Z 1200MM 4300LM TUNABLE WHITE 2700-6500K IP20 I KL. OPAL CZARNY 68W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	x	LED lifespan L90B10 [h]:	34000
EAN:	x	Diffuser material:	PMMA; PS
Light source:	moduł LED	Diffuser type:	OPAL
Rated power [W] - range:	30-53	Material of the body:	stal
Luminous flux of the luminaire [lm] - range:	1890 - 6100	Colour of the body:	biały; czarny
Supply voltage [V]:	220 - 240	Ring colour:	biały; czarny
Frequency [Hz]:	50 - 60	Dimensions (H/W/T/S) [mm]:	ø602/32; ø602/68; ø900/32; ø900/68; ø1200/32
Energy efficiency class:	D; E; F; G	Mounting dimensions [mm]:	340/340
Electrical protection class:	I	Ingress protection:	IP20
Colour temperature [K]:	3000; 4000	Mounting version:	natynkowy; zwieszany
Colour temperature [K] - range:	2700 - 6500	DIMM DALI:	yes
Colour rendering index:	>80	Cable length [m]:	1
SDCM:	≤ 3	Warranty [years]:	5
LED lifespan L70B50 [h]:	112000	CE certificate:	217/2023; 218/2023; 34/2022
LED lifespan L80B20 [h]:	70 000	Manual:	Download PDF

Card creation date: 02 October 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 218/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl