

# SOLANTO Z 1200MM 4300LM TUNABLE WHITE 2700-6500K IP20 I KL. OPAL CZARNY 68W

DETAILED CARD



## TECHNICAL PARAMETERS

Light source:	LED module
Rated power [W] - range:	62
Colour temperature [K] - range:	2700 - 6500
Luminous flux of the luminaire [lm] - range:	3900
Ingress protection:	IP20
Electrical protection class:	I
Diffuser material:	PMMA
Diffuser type:	OPAL
Colour of the body:	black

## CHARACTERISTICS

Suspended or surface-mounted ring-shaped LED luminaire, allowing for an attractive arrangement of representative interiors. The luminaire is made of steel powder coated in white, black or other color to fit the character of the interior. The milky diffuser made with thermoforming method emphasises the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings increasing the versatility and functionality of the luminaire, while reducing the number of indexes to the necessary minimum.

## APPLICATION

SOLANTO is an extremely glamorous pendant or surface mounted luminaire, dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can be also used in apartments and apartments, perfectly fitting into stylish surroundings.

# SOLANTO Z 1200MM 4300LM TUNABLE WHITE 2700-6500K IP20 I KL. OPAL CZARNY 68W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	467370	Diffuser material:	PMMA
Light source:	LED module	Diffuser type:	OPAL
Rated power [W] - range:	62	Material of the body:	Steel
Luminous flux of the luminaire [lm] - range:	3900	Colour of the body:	black
Supply voltage [V]:	220 - 240	Ring colour:	black
Frequency [Hz]:	50 - 60	Dimensions (H/W/T/S) [mm]:	ø1200/32
Luminous efficacy [lm/W]:	63	Mounting dimensions [mm]:	340/340
Energy efficiency class:	G	Ingress protection:	IP20
Electrical protection class:	I	Mounting version:	suspended
Colour temperature [K] - range:	2700 - 6500	Cable length [m]:	1.35
Colour rendering index:	>80	Net weight [kg]:	5.800
SDCM:	≤ 3	Warranty [years]:	5
LED lifespan L70B50 [h]:	112000	CE certificate:	<a href="#">218/2023</a>
LED lifespan L80B20 [h]:	70 000	Manual:	<a href="#">Download PDF</a>
LED lifespan L90B10 [h]:	34000		