

# TIUNNE PLUS 160 1310LM 840 15D WHITE IP65/IP20 REFLECTOR S 12W

---

DETAILED CARD



# TIUNNE PLUS 160 1310LM 840 15D WHITE IP65/IP20 REFLECTOR S 12W

## DETAILED CARD

### TECHNICAL PARAMETERS

<b>Index:</b>	417092
<b>Ingress protection:</b>	IP65
<b>Rated power of the luminaire [W]*:</b>	12
<b>Luminous flux [lm]*:</b>	1310
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	80
<b>Energy efficiency class:</b>	E
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	white
<b>Diffuser material:</b>	PC

### CHARACTERISTICS

Tiunne Plus is a decorative downlight luminaire for installation in suspended ceilings. It is energy-efficient and durable thanks to the COB LED light source used. It has a classic circular shape that blends in with any type of space. It is available in several versions with different light distribution angles and four reflector colours.

The lamp housing designed in aluminium ensures optimum working conditions for the LEDs, and the aluminium reflector guarantees high luminous efficiency and low glare - features that distinguish the best LED downlight luminaires. The luminaire is suitable for installation in plasterboard and modular ceilings. Colour temperature 3000K, 4000K; CRI>80, CRI>90.

### APPLICATION

The luminaire is designed for indoor use as general lighting. It is ideal for walkways, entrance areas, shop windows and fitting rooms in commercial premises.

### DETAILS

LED lifespan: L70F50 >60 000h; L80F10 >60 000h; L90F10 57 000h


# TIUNNE PLUS 160 1310LM 840 15D WHITE IP65/IP20 REFLECTOR S 12W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	417092	Optics:	reflector S
EAN:	5905963417092	Material of the body:	aluminium
Light source:	COB	Colour of the body:	white
Rated power of the luminaire [W]:	12	Ring material:	aluminium
Luminous flux [lm]:	1310	Ring colour:	white
Remarks:	S- silver matt	Dimensions (H/W/T/S) [mm]:	ø170/98
Luminous efficacy [lm/W]:	110	Mounting dimensions [mm]:	160
Energy efficiency class:	E	Ingress protection:	IP65
Electrical protection class:	II	Mounting version:	recessed
Colour temperature [K]:	4000	Net weight [kg]:	0.550
Colour rendering index:	80	Category type:	downlights
Beam angle [°]:	15	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	<a href="#">469/2023</a>
Diffuser type:	transparent	Manual:	<a href="#">Download PDF</a>
Optics material:	aluminium	Plik LDT:	<a href="#">Download</a>

## LIGHT CURVES



# TIUNNE PLUS 160 1310LM 840 15D WHITE IP65/IP20 REFLECTOR S 12W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
416835	Masking ring 198/257 Tiunne Plus 200 RAL9016
416859	Masking ring 198/257 Square Tiunne Plus 200 RAL9016

Card creation date: 23 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 469/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl