

TOWER LITE MULTIBATTERY 68W (10285LM) - GREY

DETAILED CARD



TECHNICAL PARAMETERS

Index:	250255
Ingress protection:	IP20
Impact resistance:	IK07
Rated power of the luminaire [W]*:	68
Colour temperature [K]:	4000
Luminous flux [lm]*:	10285
Supply voltage [V]:	18
Electrical protection class:	III
Colour of the body:	grey
Diffuser material:	PC

CHARACTERISTICS

A set of compact floodlights providing even and stable directional illumination. The lamp body made from co-polymer with rubber for high durability. The lamps are fitted with an anti-glare frosted PC diffuser with UV stabiliser, allowing up to 80% of the light emitted by the LEDs to pass through, despite the matt surface, providing a soft and diffuse light. The set is set on a 2-metre stand allowing easy positioning of the light and selection of the right angle for the work surface. Kit equipped with an on/off switch with 4-stage light output adjustment. Lamp compatible with 18V batteries from manufacturers such as:

- directBosch (18V Professional),
- with a dedicated adapter: Makita, Milwaukee, DeWalt, Festool, Hikoki, Metabo (CAS), Hiltl .

The unit has a battery discharge indication.

APPLICATION

Thanks to its various functions, the lamp is the ideal solution for illuminating all workplaces. The high luminous flux and maximum degree of impact resistance are particularly important for illuminating construction sites or intervening services at various emergencies. The lamp's design allows it to be used in the harshest of weather conditions. The multi-position arm provides a wide range of mounting options so that the light beam can be precisely directed, leaving the worker's hands free. Its small size and light weight make it easy to use in workshops, car showrooms, for lighting workplaces in industrial halls or finishing work.

TOWER LITE MULTIBATTERY 68W (10285LM) - GREY

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	250255	Beam angle [°]:	120
Rated power of the luminaire [W]:	68	Diffuser material:	PC
EAN:	5905963250255	Diffuser type:	MAT
Colour temperature [K]:	4000	Diffuser colour:	white
Light source:	LED	Impact resistance:	IK07
Luminous flux [lm]:	10285	Ingress protection:	IP20
Colour of the body:	grey	Dimensions of single box [mm]:	1130/263/169
Battery:	18V	Number on the palette [pcs]:	24
Tilt angle adjustment [°]:	yes	Net weight [kg]:	4.360
Supply voltage [V]:	18	Gross weight [kg]:	5
Luminous efficacy [lm/W]:	151	Category type:	workplace floodlights
Dimensions (H/W/T/S) [mm]:	1130/263/169	Warranty [years]:	5
Electrical protection class:	III	CE certificate:	470/2023
Colour rendering index:	>80	Manual:	Download PDF

TOWER LITE MULTIBATTERY 68W (10285LM) - GREY

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
249150	ACCU BOSCH 18V 2Ah
249167	ACCU BOSCH 18V 5Ah
249174	ACCU CHARGER BOSCH EU 18V 2Ah/5Ah
608803	Adapter for Magnum Battery BOSCH / MIL - DEW (NEW)
608810	Adapter for Magnum Battery BOSCH / MAKITA (NEW)
608827	Adapter for Magnum Battery BOSCH / FESTOOL (NEW)
608841	Adapter for Magnum Battery BOSCH / METABO (NEW)
608858	Adapter for Magnum Battery BOSCH / Hikoki 18V (NEW)
608834	Adapter for Magnum Battery BOSCH / Hilti 22V (NEW)
608681	Adapter for Makita 18V batteries
608650	Adapter for Milwaukee/DeWalt 18V batteries



Adapter for Magnum Battery BOSCH / MIL - DEW (NEW) (608803)



Adapter for Magnum Battery BOSCH / MAKITA (NEW) (608810)



Adapter for Magnum Battery BOSCH / FESTOOL (NEW) (608827)



Adapter for Magnum Battery BOSCH / METABO (NEW) (608841)



Adapter for Magnum Battery BOSCH / Hikoki 18V (NEW) (608858)

Card creation date: 05 October 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 470/2023