# EXTENSION CABLE REEL IP44 25 METRES H07RN-F 3X2.5MM2 (PL-FR STANDARD)

DETAILED CARD



## TECHNICAL PARAMETERS

| | |
|---|---|
| **Index:** | 612404 |
| **Supply voltage [V]:** | 220 – 240 |
| **Frequency [Hz]:** | 50 |
| **Electrical protection class:** | I |
| **Colour of the body:** | black |
| **Ingress protection:** | IP44 |
| **Working temperature [°C]:** | from -20 to +35 |
| **Plug type:** | UNI-SCHUKO |
| **Socket type:** | PL-FR |
| **Sockets:** | 4 |

## CHARACTERISTICS

Regardless of the length of the cable, they allow it to be unwound and retracted quickly. Thanks to their clever design, extension cords are comfortable to use and significantly improve working comfort. The extension cable is suitable for use in the workshop or on the construction site, as well as for domestic and garden use. The extension cord has a built-in thermal switch which protects against overheating. The IP44-rated sockets are fitted with a flap - suitable for outdoor use in various weather conditions. The reel has a cable holder and a brake to avoid accidental over-extension of the overextension. It is ideal for connecting any electrical consumer such as: power tools, lawnmowers, hoovers, construction equipment, etc. It is made of flexible cable for easy retraction.
Thermal protection: YES
Maximum load for coiled extension cord: 1100W
Maximum load for extension cord unrolled: 3200W

## APPLICATION

Professional construction extension cords are specialised extension cords designed for use on construction sites or in workshops.

# EXTENSION CABLE REEL IP44 25 METRES H07RN-F 3X2.5MM2 (PL-FR STANDARD)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

| | |
|---|---|
| **Index:** | 612404 |
| **Category type:** | electrical materials |
| **Supply voltage [V]:** | 220 – 240 |
| **Frequency [Hz]:** | 50 |
| **Electrical protection class:** | I |
| **Colour of the body:** | black |
| **Ingress protection:** | IP44 |
| **Working temperature [°C]:** | from -20 to +35 |
| **Plug type:** | UNI-SCHUKO |

| | |
|---|---|
| **Socket type:** | PL-FR |
| **Sockets:** | 4 |
| **Wire type:** | H07RN-F 3x2.5mm |
| **Cable length [m]:** | 25 |
| **Dimensions (H/W/T/S) [mm]:** | 275/185/370 |
| **Warranty [years]:** | 2 |
| **Manual:** | Download PDF |
| **CE certificate:** | 471/2023 |

Card creation date: 06 October 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 471/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl