

EXTENSION CABLE REEL IP44 25 METRES H07RN-F 3X2.5MM2 (PL-FR STANDARD)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	612404
Supply voltage [V]:	220 – 240
Frequency [Hz]:	50
Electrical protection class:	I
Colour of the body:	black
Ingress protection:	IP44
Working temperature [°C]:	from -20 to +35
Plug type:	UNI-SCHUKO
Socket type:	PL-FR
Sockets:	4

CHARACTERISTICS

Regardless of the length of the cable, they allow it to be unwound and retracted quickly. Thanks to their clever design, extension cords are comfortable to use and significantly improve working comfort. The extension cable is suitable for use in the workshop or on the construction site, as well as for domestic and garden use. The extension cord has a built-in thermal switch which protects against overheating. The IP44-rated sockets are fitted with a flap - suitable for outdoor use in various weather conditions. The reel has a cable holder and a brake to avoid accidental over-extension of the overextension. It is ideal for connecting any electrical consumer such as: power tools, lawnmowers, hoovers, construction equipment, etc. It is made of flexible cable for easy retraction.

Thermal protection: YES
Maximum load for coiled extension cord: 1100W
Maximum load for extension cord unrolled: 3200W

APPLICATION

Professional construction extension cords are specialised extension cords designed for use on construction sites or in workshops.

EXTENSION CABLE REEL IP44 25 METRES H07RN-F 3X2.5MM2 (PL-FR STANDARD)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	612404	Socket type:	PL-FR
Category type:	electrical materials	Sockets:	4
Supply voltage [V]:	220 – 240	Wire type:	H07RN-F 3x2.5mm
Frequency [Hz]:	50	Cable length [m]:	25
Electrical protection class:	I	Dimensions (H/W/T/S) [mm]:	275/185/370
Colour of the body:	black	Warranty [years]:	2
Ingress protection:	IP44	Manual:	Download PDF
Working temperature [°C]:	from -20 to +35	CE certificate:	471/2023
Plug type:	UNI-SCHUKO		

Card creation date: 06 October 2023
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 471/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl