MULTI LIGHT LED

DETAILED CARD





TECHNICAL PARAMETERS

Index:	608759
--------	--------

Ingress protection: IP20

Supply voltage [V]: 3.6

Electrical protection class:

Color rendering index (Ra) >: 80

Charging time [h:min]: 4

Battery life [h:min]: min 1.5- max 40

2 pcs Li-lon 2600mAh 3.6V 5A (9.36Wh) rechargeable batteries

with C-type charging input - can be charged

outside the lamp

Dimensions (H/W/T/S) [mm]: 420/300/250

CHARACTERISTICS

The torch and work light set is the perfect solution for mechanics, craftsmen and DIY enthusiasts. It is a state-of-the-art work light system that allows various light tips to be mounted on a single base (with battery). A professional set of lamps for illumination during work. Particularly suitable for servicing cars, vans and trucks. The set consists of a base and various attachable tips with bayonet connector. The replaceable rechargeable battery can be charged separately (outside of the lamp) using a C-connector.

Flashlight-type tip - max. 273 Lm SLIM hand lamp nozzle - max. 385 Lm Flexible tip with light source - max. 199Lm Slim flexible tip with light source - max. 3 Lm Battery life [h:min]

Flashlight-type nozzle - LOW level 139 Lm / 5h; POWER level 273 Lm / 2.5h SLIM hand lamp-type nozzle - LOW level 192 Lm / 4h; POWER level 385 Lm / 1.5h Flexible nozzle with light source - LOW level 99 Lm / 8h; POWER level 199 Lm / 5h Slim flexible nozzle with light source - LOW level 1.50 Lm / 80h ; POWER level 3.00 Lm / 40h

APPLICATION

Car services (car, van and truck repairs), detailing salons, car washes, mobile services, etc.



Battery:

MULTI LIGHT LED

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	608759
EAN:	5905963608759
Light source:	LED
Luminous flux of the luminaire [lm] - range:	3-385
Supply voltage [V]:	3.6
Electrical protection class:	III
Color rendering index (Ra) >:	80
Charging time [h:min]:	4
Battery life [h:min]:	min 1.5- max 40
Light colour:	biały
Battery:	2 pcs Li-lon 2600mAh 3.6V 5A (9.36Wh) rechargeable batteries with C-type charging input - can be charged outside the lamp
Battery capacity [mAh]:	2600

Diffuser type:	transparent
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	420/300/250
Ingress protection:	IP20
Working temperature [°C]:	od -20 do +35
Switch:	yes
Magnet:	yes
Net weight [kg]:	0.940
Accessories included:	2 pcs Li-lon 2600mAh 3.6V 5A (9.36Wh) rechargeable batteries with C-type charging input - can be charged outside the lamp
Category type:	portable led fittings
CE certificate:	<u>472/2023</u>
Manual:	Download PDF

Card creation date: 09 October 2023





Certificate CE - Nr: 472/2023