

MULTI LIGHT LED

DETAILED CARD



TECHNICAL PARAMETERS

Index:	608759
Ingress protection:	IP20
Supply voltage [V]:	3.6
Electrical protection class:	III
Colour rendering index:	> 80
Charging time [h:min]:	4
Battery life [h:min]:	min 1.5- max 40
Battery:	2 pcs Li-Ion 2600mAh 3.6V 5A (9.36Wh) rechargeable batteries with C-type charging input - can be charged outside the lamp
Dimensions (H/W/T/S) [mm]:	420/300/250

CHARACTERISTICS

The torch and work light set is the perfect solution for mechanics, craftsmen and DIY enthusiasts. It is a state-of-the-art work light system that allows various light tips to be mounted on a single base (with battery). A professional set of lamps for illumination during work. Particularly suitable for servicing cars, vans and trucks. The set consists of a base and various attachable tips with bayonet connector. The replaceable rechargeable battery can be charged separately (outside of the lamp) using a C-connector.

Flashlight-type tip - max. 273 Lm
SLIM hand lamp nozzle - max. 385 Lm
Flexible tip with light source - max. 199Lm
Slim flexible tip with light source - max. 3 Lm

Battery life [h:min]

Flashlight-type nozzle - LOW level 139 Lm / 5h; POWER level 273 Lm / 2.5h
SLIM hand lamp-type nozzle - LOW level 192 Lm / 4h; POWER level 385 Lm / 1.5h
Flexible nozzle with light source - LOW level 99 Lm / 8h; POWER level 199 Lm / 5h
Slim flexible nozzle with light source - LOW level 1.50 Lm / 80h ; POWER level 3.00 Lm / 40h

APPLICATION

Car services (car, van and truck repairs), detailing salons, car washes, mobile services, etc.

MULTI LIGHT LED

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	608759	Diffuser type:	transparent
EAN:	5905963608759	Colour of the body:	black
Light source:	LED	Dimensions (H/W/T/S) [mm]:	420/300/250
Luminous flux of the luminaire [lm] - range:	3-385	Ingress protection:	IP20
Supply voltage [V]:	3.6	Working temperature [°C]:	from -20°C to +35°C
Electrical protection class:	III	Switch:	yes
Colour rendering index:	> 80	Magnet:	yes
Charging time [h:min]:	4	Net weight [kg]:	0.940
Battery life [h:min]:	min 1.5- max 40	Accessories included:	2 pcs Li-Ion 2600mAh 3.6V 5A (9.36Wh) rechargeable batteries with C-type charging input - can be charged outside the lamp
Light colour:	biały	Category type:	portable led fittings
Battery:	2 pcs Li-Ion 2600mAh 3.6V 5A (9.36Wh) rechargeable batteries with C-type charging input - can be charged outside the lamp	CE certificate:	472/2023
Battery capacity [mAh]:	2600	Manual:	Download PDF

Card creation date: 09 October 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 472/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl