

TIUNNE PLUS 160 2500LM 930 DALI 60D BLACK IP65/IP20 REFLECTOR B 31W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	431364
Ingress protection:	IP65/IP20
Rated power of the luminaire [W]*:	31
Luminous flux [lm]*:	2500
Colour temperature [K]:	3000
Colour rendering index:	>90
Energy efficiency class:	F
Material of the body:	aluminium
Colour of the body:	white
Diffuser material:	PC

CHARACTERISTICS

Tiunne Plus is a decorative downlight luminaire for installation in suspended ceilings. It is energy-efficient and durable thanks to the COB LED light source used. It has a classic circular shape that blends in with any type of space. It is available in several versions with different light distribution angles and four reflector colours.

The lamp housing designed in aluminium ensures optimum working conditions for the LEDs, and the aluminium reflector guarantees high luminous efficiency and low glare - features that distinguish the best LED downlight luminaires. The luminaire is suitable for installation in plasterboard and modular ceilings. Colour temperature 3000K, 4000K; CRI>80, CRI>90.

APPLICATION

The luminaire is designed for indoor use as general lighting. It is ideal for walkways, entrance areas, shop windows and fitting rooms in commercial premises.

DETAILS

LED lifespan: L70F50 >60 000h; L80F10 >60 000h; L90F10 57 000h


TIUNNE PLUS 160 2500LM 930 DALI 60D BLACK IP65/IP20 REFLECTOR B 31W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	31	Material of the body:	aluminium
Index:	431364	Dimensions (H/W/T/S) [mm]:	ø170/98
Colour temperature [K]:	3000	Colour of the body:	white
EAN:	5905963431364	Ring material:	aluminium
Luminous flux [lm]:	2500	Mounting dimensions [mm]:	88
Light source:	COB	Ingress protection:	IP65/IP20
Remarks:	B- black matt	DIMM DALI:	yes
Luminous efficacy [lm/W]:	81	Mounting version:	recessed
Energy efficiency class:	F	Working temperature [°C]:	35
Colour rendering index:	>90	Net weight [kg]:	0.250
Electrical protection class:	II	Category type:	downlights
Beam angle [°]:	60	Light colour:	3000
Optics:	reflector B	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	469/2023
Diffuser type:	transparent	Manual:	Download PDF
Optics material:	aluminium		
Ring colour:	black		

LIGHT CURVES



TIUNNE PLUS 160 2500LM 930 DALI 60D BLACK IP65/IP20 REFLECTOR B 31W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
416835	Masking ring 198/257 Tiunne Plus 200 RAL9016
416859	Masking ring 198/257 Square Tiunne Plus 200 RAL9016

Card creation date: 23 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 469/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl