

# TIUNNE PLUS 160 890LM 840 60D BLACK IP65/IP20 REFLECTOR GS 8W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	431449
<b>Ingress protection:</b>	IP65/IP20
<b>Rated power of the luminaire [W]*:</b>	8
<b>Luminous flux [lm]*:</b>	890
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	>80
<b>Energy efficiency class:</b>	E
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	white
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

Tiunne Plus is a decorative downlight luminaire for installation in suspended ceilings. It is energy-efficient and durable thanks to the COB LED light source used. It has a classic circular shape that blends in with any type of space. It is available in several versions with different light distribution angles and four reflector colours.

The lamp housing designed in aluminium ensures optimum working conditions for the LEDs, and the aluminium reflector guarantees high luminous efficiency and low glare - features that distinguish the best LED downlight luminaires. The luminaire is suitable for installation in plasterboard and modular ceilings. Colour temperature 3000K, 4000K; CRI>80, CRI>90.

## APPLICATION

The luminaire is designed for indoor use as general lighting. It is ideal for walkways, entrance areas, shop windows and fitting rooms in commercial premises.

## DETAILS

LED lifespan: L70F50 >60 000h; L80F10 >60 000h; L90F10 57 000h


# TIUNNE PLUS 160 890LM 840 60D BLACK IP65/IP20 REFLECTOR GS 8W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	8	Material of the body:	aluminium
Index:	431449	Dimensions (H/W/T/S) [mm]:	ø170/98
Colour temperature [K]:	4000	Colour of the body:	white
EAN:	5905963431449	Ring material:	aluminium
Luminous flux [lm]:	890	Mounting dimensions [mm]:	88
Light source:	COB	Ingress protection:	IP65/IP20
Remarks:	GS - glossy silver	Mounting version:	recessed
Luminous efficacy [lm/W]:	112	Working temperature [°C]:	35
Energy efficiency class:	E	Net weight [kg]:	0.250
Colour rendering index:	>80	Category type:	downlights
Electrical protection class:	II	Light colour:	4000
Beam angle [°]:	60	Warranty [years]:	5
Optics:	reflector GS	CE certificate:	<a href="#">469/2023</a>
Diffuser material:	PC	Manual:	<a href="#">Download PDF</a>
Diffuser type:	transparent		
Optics material:	aluminium		
Ring colour:	black		

## LIGHT CURVES



# TIUNNE PLUS 160 890LM 840 60D BLACK IP65/IP20 REFLECTOR GS 8W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
416835	Masking ring 198/257 Tiunne Plus 200 RAL9016
416859	Masking ring 198/257 Square Tiunne Plus 200 RAL9016

Card creation date: 23 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 469/2023