

TIUNNE PLUS 90 1180LM 840 15D BLACK IP65/IP20 REFLECTOR B 14W

DETAILED CARD



TIUNNE PLUS 90 1180LM 840 15D BLACK IP65/IP20 REFLECTOR B 14W

DETAILED CARD

TECHNICAL PARAMETERS

Index:	430275
Ingress protection:	IP65/IP20
Rated power of the luminaire [W]*:	14
Luminous flux [lm]*:	1180
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Energy efficiency class:	F
Material of the body:	aluminium
Colour of the body:	white
Diffuser material:	PC

CHARACTERISTICS

Tiunne Plus is a decorative downlight luminaire for installation in suspended ceilings. It is energy-efficient and durable thanks to the COB LED light source used. It has a classic circular shape that blends in with any type of space. It is available in several versions with different light distribution angles and four reflector colours.

The lamp housing designed in aluminium ensures optimum working conditions for the LEDs, and the aluminium reflector guarantees high luminous efficiency and low glare - features that distinguish the best LED downlight luminaires. The luminaire is suitable for installation in plasterboard and modular ceilings. Colour temperature 3000K, 4000K; CRI>80, CRI>90.

APPLICATION

The luminaire is designed for indoor use as general lighting. It is ideal for walkways, entrance areas, shop windows and fitting rooms in commercial premises.

DETAILS

LED lifespan: L70F50 >60 000h; L80F10 >60 000h; L90F10 57 000h


TIUNNE PLUS 90 1180LM 840 15D BLACK IP65/IP20 REFLECTOR B 14W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	430275	Material of the body:	aluminium
EAN:	5905963430275	Colour of the body:	white
Light source:	COB	Ring material:	aluminium
Rated power of the luminaire [W]:	14	Ring colour:	black
Luminous flux [lm]:	1180	Dimensions (H/W/T/S) [mm]:	ø96/73
Remarks:	B- black matt	Mounting dimensions [mm]:	88
Luminous efficacy [lm/W]:	85	Ingress protection:	IP65/IP20
Energy efficiency class:	F	Mounting version:	recessed
Electrical protection class:	II	Working temperature [°C]:	35
Colour temperature [K]:	4000	Net weight [kg]:	0.250
Color rendering index (Ra) >:	80	Category type:	downlights
Beam angle [°]:	15	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	18/2026
Diffuser type:	transparent	Manual:	Download PDF
Optics material:	aluminium	Plik LDT:	Download
Optics:	reflector B		

LIGHT CURVES



TIUNNE PLUS 90 1180LM 840 15D BLACK IP65/IP20 REFLECTOR B 14W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
416835	Masking ring 198/257 Tiunne Plus 200 RAL9016
416859	Masking ring 198/257 Square Tiunne Plus 200 RAL9016

Card creation date: 23 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 18/2026



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl