## TIUNNE PLUS 90 1210LM 830 DALI 15D WHITE IP65/IP20 REFLECTOR GS 16W

**DETAILED CARD** 





## **TECHNICAL PARAMETERS**

**Index:** 429347

Ingress protection: IP65/IP20

Rated power of the luminaire [W]\*: 16

Luminous flux [lm]\*: 1210

Colour temperature [K]: 3000

Colour rendering index: >80

Energy efficiency class:

Material of the body: aluminium

Colour of the body: white

Diffuser material: PC

## **CHARACTERISTICS**

Tiunne Plus is a decorative downlight luminaire for installation in suspended ceilings. It is energy-efficient and durable thanks to the COB LED light source used. It has a classic circular shape that blends in with any type of space. It is available in several versions with different light distribution angles and four reflector colours.

The lamp housing designed in aluminium ensures optimum working conditions for the LEDs, and the aluminium reflector guarantees high luminous efficiency and low glare - features that distinguish the best LED downlight luminaires. The luminaire is suitable for installation in plasterboard and modular ceilings. Colour temperature 3000K, 4000K; CRI>80, CRI>90.

#### **APPLICATION**

The luminaire is designed for indoor use as general lighting. It is ideal for walkways, entrance areas, shop windows and fitting rooms in commercial premises.

## **DETAILS**

Żywotność LED: L70F50 >60 000h; L80F10 >60 000h; L90F10 57 000h



# TIUNNE PLUS 90 1210LM 830 DALI 15D WHITE IP65/IP20 REFLECTOR GS 16W

**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

Index:	429347
EAN:	5905963429347
Light source:	СОВ
Rated power of the luminaire [W]:	16
Luminous flux [Im]:	1210
Luminous efficacy [lm/W]:	76
Energy efficiency class:	F
Electrical protection class:	II
Colour temperature [K]:	3000
Colour rendering index:	>80
Beam angle [°]:	15
Diffuser material:	PC
Diffuser type:	transparent
Optics material:	aluminium
Optics:	reflector GS
Remarks:	GS - glossy silver

Material of the body:	aluminium
Colour of the body:	white
Ring material:	aluminium
Ring colour:	white
Dimensions (H/W/T/S) [mm]:	96/96/73
Mounting dimensions [mm]:	88
Ingress protection:	IP65/IP20
Mounting version:	recessed
Working temperature [°C]:	35
DIMM DALI:	yes
Net weight [kg]:	0.250
Category type:	downlights
Warranty [years]:	5
CE certificate:	469/2023
Manual:	Download PDF

Card creation date: 25 March 2024



