# TERRA 3 LED N 1195X170MM X2 5150LM 830 BLACK MATT STRUCTURE (45W)

**DETAILED CARD** 





### **TECHNICAL PARAMETERS**

Index: 428852

Rated power of the luminaire [W]\*: 45

Luminous flux [lm]\*: 5150

Colour temperature [K]: 3000

Colour rendering index: 80

Material of the body: powder coated steel

Colour of the body: black mat

**Dimensions (H/W/T/S) [mm]:** 1195/170/37

Mounting version: surface

Energy efficiency class:

### **CHARACTERISTICS**

A luminaire equipped with energy-efficient LED modules characterised by high luminous flux. The low side profile provides an aesthetically pleasing, timeless appearance. Robust, compact construction. Made of powder-coated steel sheet. Patented high-performance HE reflector guarantees high efficiency while effectively eliminating glare.

## **APPLICATION**

The versatile luminaire is designed for indoor use in offices or general utility rooms. Its high luminous parameters make it suitable as the main source of light and conducive to work requiring visual focus. The luminaire is suitable for both new applications and the replacement of traditional fluorescent lamps with energy-efficient LED solutions.



# TERRA 3 LED N 1195X170MM X2 5150LM 830 BLACK MATT STRUCTURE (45W)


**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

EAN: 5905963428852  Light source: LED  Rated power of the luminaire [W]: 45  Luminous flux [Im]: 5150  Luminous efficacy [Im/W]: 114  Ingress protection: IP20  Energy efficiency class: F  Electrical protection class: II  Colour temperature [K]: 3000  Colour rendering index: 80  Beam angle [°]: 60  Diffuser material: PC  Diffuser type: matrix led  Diffuser colour: transparent  Optics material: PC  Optics: lens	Index:	428852
Light source:  Rated power of the luminaire [W]:  Luminous flux [Im]:  Luminous efficacy [Im/W]:  Ingress protection:  Energy efficiency class:  Electrical protection class:  Colour temperature [K]:  Colour rendering index:  Beam angle [°]:  Diffuser material:  Diffuser type:  matrix led  Diffuser colour:  Optics material:  PC		
Rated power of the luminaire [W]:  Luminous flux [Im]:  5150  Luminous efficacy [Im/W]:  Ingress protection:  Energy efficiency class:  Electrical protection class:  II  Colour temperature [K]:  Colour rendering index:  Beam angle [°]:  Diffuser material:  Diffuser type:  matrix led  Diffuser colour:  Optics material:  PC	EAN:	5905963428852
Luminous flux [lm]:  Luminous efficacy [lm/W]:  Ingress protection:  Energy efficiency class:  Electrical protection class:  Colour temperature [K]:  Colour rendering index:  Beam angle [°]:  Diffuser material:  Diffuser type:  Diffuser colour:  Optics material:  PC	Light source:	LED
Luminous efficacy [Im/W]:  Ingress protection:  Energy efficiency class:  Electrical protection class:  Colour temperature [K]:  Colour rendering index:  Beam angle [°]:  Diffuser material:  Diffuser type:  matrix led  Diffuser colour:  Optics material:  PC	Rated power of the luminaire [W]:	45
Ingress protection:  Energy efficiency class:  Electrical protection class:  Colour temperature [K]:  Colour rendering index:  Beam angle [°]:  Diffuser material:  Diffuser type:  matrix led  Diffuser colour:  Optics material:  PC	Luminous flux [lm]:	5150
Energy efficiency class:  Electrical protection class:  Colour temperature [K]:  Colour rendering index:  Beam angle [°]:  Diffuser material:  Diffuser type:  Diffuser colour:  Optics material:  PC	Luminous efficacy [lm/W]:	114
Electrical protection class:  Colour temperature [K]:  Colour rendering index:  80  Beam angle [°]:  Diffuser material:  Diffuser type:  Diffuser colour:  Optics material:  PC	Ingress protection:	IP20
Colour temperature [K]:  Colour rendering index:  80  Beam angle [°]:  Diffuser material:  PC  Diffuser type:  Diffuser colour:  Optics material:  PC	Energy efficiency class:	F
Colour rendering index:  Beam angle [°]:  Diffuser material:  Diffuser type:  Diffuser colour:  Optics material:  PC  80  PC  matrix led  transparent  PC	Electrical protection class:	Ш
Beam angle [°]:  Diffuser material:  PC  Diffuser type:  matrix led  Diffuser colour:  transparent  Optics material:  PC	Colour temperature [K]:	3000
Diffuser material:  Diffuser type:  matrix led  transparent  Optics material:  PC  PC	Colour rendering index:	80
Diffuser type: matrix led Diffuser colour: transparent Optics material: PC	Beam angle [°]:	60
Diffuser colour: transparent Optics material: PC	Diffuser material:	PC
Optics material: PC	Diffuser type:	matrix led
·	Diffuser colour:	transparent
Optics: lens	Optics material:	PC
	Optics:	lens

Material of the body:	powder coated steel
Colour of the body:	black mat
Dimensions (H/W/T/S) [mm]:	1195/170/37
Mounting version:	surface
Number on the palette [pcs]:	60
Net weight [kg]:	1.600
Category type:	troffers
Version:	2x1
Mounting dimensions [mm]:	600
Light distribution type:	symmetric
LED lifespan L70B50 [h]:	150000
LED lifespan L80B20 [h]:	100000
LED lifespan L90B10 [h]:	50000
Warranty [years]:	5
CE certificate:	61/2025
Manual:	Download PDF
Plik LDT:	Download

### **LIGHT CURVES**





# TERRA 3 LED N 1195X170MM X2 5150LM 830 BLACK MATT STRUCTURE (45W)


**DETAILED CARD** 

### **ACCESSORIES AVAILABLE**

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"







Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

