


TERRA 3 LED N 1195X170MM X4 5800LM 830 WHITE MAT (40W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|------------------------------------|---------------------|
| Index: | 428289 |
| Rated power of the luminaire [W]*: | 40 |
| Luminous flux [lm]*: | 5800 |
| Colour temperature [K]: | 3000 |
| Colour rendering index: | 80 |
| Material of the body: | powder coated steel |
| Colour of the body: | white mat |
| Dimensions (H/W/T/S) [mm]: | 1195/170/37 |
| Mounting version: | surface |
| Energy efficiency class: | C |

CHARACTERISTICS

A luminaire equipped with energy-efficient LED modules characterised by high luminous flux. The low side profile provides an aesthetically pleasing, timeless appearance. Robust, compact construction. Made of powder-coated steel sheet. Patented high-performance HE reflector guarantees high efficiency while effectively eliminating glare.

APPLICATION

The versatile luminaire is designed for indoor use in offices or general utility rooms. Its high luminous parameters make it suitable as the main source of light and conducive to work requiring visual focus. The luminaire is suitable for both new applications and the replacement of traditional fluorescent lamps with energy-efficient LED solutions.

TERRA 3 LED N 1195X170MM X4 5800LM 830 WHITE MAT (40W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|------------------------------|------------------------------|
| Index: | 428289 | Material of the body: | powder coated steel |
| EAN: | 5905963428289 | Colour of the body: | white mat |
| Light source: | LED | Dimensions (H/W/T/S) [mm]: | 1195/170/37 |
| Rated power of the luminaire [W]: | 40 | Mounting version: | surface |
| Luminous flux [lm]: | 5800 | Number on the palette [pcs]: | 100 |
| Luminous efficacy [lm/W]: | 145 | Net weight [kg]: | 1.600 |
| Ingress protection: | IP20 | Category type: | troffers |
| Energy efficiency class: | C | Version: | 4x1 |
| Electrical protection class: | II | Mounting dimensions [mm]: | 600 |
| Colour temperature [K]: | 3000 | Light distribution type: | symmetric |
| Colour rendering index: | 80 | LED lifespan L70B50 [h]: | 150000 |
| Beam angle [°]: | 60 | LED lifespan L80B20 [h]: | 100000 |
| Diffuser material: | PC | LED lifespan L90B10 [h]: | 50000 |
| Diffuser type: | matrix led | Warranty [years]: | 5 |
| Diffuser colour: | transparent | CE certificate: | 61/2025 |
| Optics material: | PC | Manual: | Download PDF |
| Optics: | lens | Plik LDT: | Download |

LIGHT CURVES



TERRA 3 LED N 1195X170MM X4 5800LM 830 WHITE MAT (40W)

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|--|
| 999543 | Plasterboard recessing kit 630x630 white (steel version) |
| 374845 | Frame adapter KG 635x635 WHITE |
| 998966 | Frame steel white structure RAL9016 600x600 SM "well effect" |



Plasterboard recessing kit 630x630 white (steel version) (999543)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

Card creation date: 01 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 61/2025



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl