TERRA 3 LED N 1195X300MM X2 3300LM 830 DALI WHITE MAT (25W)

DETAILED CARD





TECHNICAL PARAMETERS

Index: 427923

Rated power of the luminaire [W]*: 25

Luminous flux [lm]*: 3300

Colour temperature [K]: 3000

Color rendering index (Ra) >: 80

Material of the body: powder coated steel

Colour of the body: white mat

Dimensions (H/W/T/S) [mm]: 1195/300/37

Mounting version: surface

Energy efficiency class: D

CHARACTERISTICS

A luminaire equipped with energy-efficient LED modules characterised by high luminous flux. The low side profile provides an aesthetically pleasing, timeless appearance. Robust, compact construction. Made of powder-coated steel sheet. Patented high-performance HE reflector guarantees high efficiency while effectively eliminating glare.

APPLICATION

The versatile luminaire is designed for indoor use in offices or general utility rooms. Its high luminous parameters make it suitable as the main source of light and conducive to work requiring visual focus. The luminaire is suitable for both new applications and the replacement of traditional fluorescent lamps with energy-efficient LED solutions.



TERRA 3 LED N 1195X300MM X2 3300LM 830 DALI WHITE MAT (25W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	427923
EAN:	5905963427923
Light source:	LED
Rated power of the luminaire [W]:	25
Luminous flux [lm]:	3300
Luminous efficacy [lm/W]:	132
Ingress protection:	IP20
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Beam angle [°]:	60
Diffuser material:	PC
Diffuser type:	matrix led
Diffuser colour:	transparent
Optics material:	PC
Optics:	lens
Material of the body:	powder coated steel

Dimensions (H/W/T/S) [mm]: 1195/300/37 Mounting version: surface DIMM DALI: yes Number on the palette [pcs]: 30 Net weight [kg]: 2.465 Category type: troffers Version: 2x1 Mounting dimensions [mm]: 600 Light distribution type: symmetric LED lifespan L70B50 [h]: 150000 LED lifespan L80B20 [h]: 100000 LED lifespan L90B10 [h]: 50000 Warranty [years]: 5 CE certificate: 61/2025 Manual: Download PDF	Colour of the body:	white mat	
DIMM DALI: yes Number on the palette [pcs]: 30 Net weight [kg]: 2.465 Category type: troffers Version: 2x1 Mounting dimensions [mm]: 600 Light distribution type: symmetric LED lifespan L70B50 [h]: 150000 LED lifespan L80B20 [h]: 100000 LED lifespan L90B10 [h]: 50000 Warranty [years]: 5 CE certificate: 61/2025 Manual: Download PDF	Dimensions (H/W/T/S) [mm]:	1195/300/37	
Number on the palette [pcs]: 30 Net weight [kg]: 2.465 Category type: troffers Version: 2x1 Mounting dimensions [mm]: 600 Light distribution type: symmetric LED lifespan L70B50 [h]: 150000 LED lifespan L80B20 [h]: 100000 LED lifespan L90B10 [h]: 50000 Warranty [years]: 5 CE certificate: 61/2025 Manual: Download PDF	Mounting version:	surface	
Net weight [kg]: 2.465 Category type: troffers Version: 2x1 Mounting dimensions [mm]: 600 Light distribution type: symmetric LED lifespan L70B50 [h]: 150000 LED lifespan L80B20 [h]: 100000 LED lifespan L90B10 [h]: 50000 Warranty [years]: 5 CE certificate: 61/2025 Manual: Download PDF	DIMM DALI:	yes	
Category type: troffers Version: 2x1 Mounting dimensions [mm]: 600 Light distribution type: symmetric LED lifespan L70B50 [h]: 150000 LED lifespan L80B20 [h]: 100000 LED lifespan L90B10 [h]: 50000 Warranty [years]: 5 CE certificate: 61/2025 Manual: Download PDF	Number on the palette [pcs]:	30	
Version: 2x1 Mounting dimensions [mm]: 600 Light distribution type: symmetric LED lifespan L70B50 [h]: 150000 LED lifespan L80B20 [h]: 100000 LED lifespan L90B10 [h]: 50000 Warranty [years]: 5 CE certificate: 61/2025 Manual: Download PDF	Net weight [kg]:	2.465	
Mounting dimensions [mm]: Light distribution type: Symmetric LED lifespan L70B50 [h]: LED lifespan L80B20 [h]: LED lifespan L90B10 [h]: Warranty [years]: CE certificate: Manual: 600 Symmetric 150000 50000 61/2025 Download PDF	Category type:	troffers	
Light distribution type: symmetric LED lifespan L70B50 [h]: 150000 LED lifespan L80B20 [h]: 100000 LED lifespan L90B10 [h]: 50000 Warranty [years]: 5 CE certificate: 61/2025 Manual: Download PDF	Version:	2x1	
LED lifespan L70B50 [h]: 150000 LED lifespan L80B20 [h]: 100000 LED lifespan L90B10 [h]: 50000 Warranty [years]: 5 CE certificate: 61/2025 Manual: Download PDF	Mounting dimensions [mm]:	600	
LED lifespan L80B20 [h]: 100000 LED lifespan L90B10 [h]: 50000 Warranty [years]: 5 CE certificate: 61/2025 Manual: Download PDF	Light distribution type:	symmetric	
LED lifespan L90B10 [h]: 50000 Warranty [years]: 5 CE certificate: 61/2025 Manual: Download PDF	LED lifespan L70B50 [h]:	150000	
Warranty [years]: 5 CE certificate: 61/2025 Manual: Download PDF	LED lifespan L80B20 [h]:	100000	
CE certificate: 61/2025 Manual: Download PDF	LED lifespan L90B10 [h]:	50000	
Manual: Download PDF	Warranty [years]:	5	
	CE certificate:	61/2025	
DIII I DT	Manual:	Download PDF	
Plik LD1: Download	Plik LDT:	Download	

LIGHT CURVES







TERRA 3 LED N 1195X300MM X2 3300LM 830 DALI WHITE MAT (25W)


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"







Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

