


# TERRA 3 LED N 1195X300MM X2 3900LM 830 DALI BLACK MATT STRUCTURE (34W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	428135
Rated power of the luminaire [W]*:	34
Luminous flux [lm]*:	3900
Colour temperature [K]:	3000
Colour rendering index:	80
Material of the body:	powder coated steel
Colour of the body:	black mat
Dimensions (H/W/T/S) [mm]:	1195/300/37
Mounting version:	surface
Energy efficiency class:	E

## CHARACTERISTICS

A luminaire equipped with energy-efficient LED modules characterised by high luminous flux. The low side profile provides an aesthetically pleasing, timeless appearance. Robust, compact construction. Made of powder-coated steel sheet. Patented high-performance HE reflector guarantees high efficiency while effectively eliminating glare.

## APPLICATION

The versatile luminaire is designed for indoor use in offices or general utility rooms. Its high luminous parameters make it suitable as the main source of light and conducive to work requiring visual focus. The luminaire is suitable for both new applications and the replacement of traditional fluorescent lamps with energy-efficient LED solutions.

# TERRA 3 LED N 1195X300MM X2 3900LM 830 DALI BLACK MATT STRUCTURE (34W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	428135	Colour of the body:	black mat
EAN:	5905963428135	Dimensions (H/W/T/S) [mm]:	1195/300/37
Light source:	LED	Mounting version:	surface
Rated power of the luminaire [W]:	34	DIMM DALI:	yes
Luminous flux [lm]:	3900	Number on the palette [pcs]:	30
Luminous efficacy [lm/W]:	115	Net weight [kg]:	2.465
Ingress protection:	IP20	Category type:	troffers
Energy efficiency class:	E	Version:	2x1
Electrical protection class:	II	Mounting dimensions [mm]:	600
Colour temperature [K]:	3000	Light distribution type:	symmetric
Colour rendering index:	80	LED lifespan L70B50 [h]:	150000
Beam angle [°]:	60	LED lifespan L80B20 [h]:	100000
Diffuser material:	PC	LED lifespan L90B10 [h]:	50000
Diffuser type:	matrix led	Warranty [years]:	5
Diffuser colour:	transparent	CE certificate:	<a href="#">61/2025</a>
Optics material:	PC	Manual:	<a href="#">Download PDF</a>
Optics:	lens	Plik LDT:	<a href="#">Download</a>
Material of the body:	powder coated steel		

## LIGHT CURVES



# TERRA 3 LED N 1195X300MM X2 3900LM 830 DALI BLACK MATT STRUCTURE (34W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"



Plasterboard recessing kit 630x630 white (steel version) (999543)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

Card creation date: 01 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 61/2025



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl