

# PROFI LED 4W PC TRANSPARENT WITH UNIVERSAL PLUG

DETAILED CARD



## TECHNICAL PARAMETERS

---

<b>Nominal power [W]:</b>	4
<b>Luminous flux [lm]*:</b>	450
<b>Colour temperature [K]:</b>	4000
<b>Ingress protection:</b>	IP54
<b>Supply voltage [V]:</b>	220 - 240
<b>Frequency [Hz]:</b>	50 - 60
<b>Electrical protection class:</b>	II
<b>Colour rendering index:</b>	>80
<b>Material of the body:</b>	gum
<b>Dimensions (H/W/T/S) [mm]:</b>	60/415

## CHARACTERISTICS

---

- Power: 4W- Luminous flux: 450lm- 65% less power consumption (compared to Profi 11W)- Light source: SMD LED- Polycarbonate impact-resistant prismatic diffuser- Handle and cap made of rubber- High ingress protection class IP54- Rotating hook- Weight: 0,7 kg- Rubber cable H05RN-F 2x1 mm<sup>2</sup> (5m)- Spare parts available

## APPLICATION

---

# PROFI LED 4W PC TRANSPARENT WITH UNIVERSAL PLUG

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	260834	<b>Colour of the body:</b>	black
<b>Nominal power [W]:</b>	4	<b>Plug type:</b>	UNI-SCHUKO
<b>EAN:</b>	5905963260834	<b>Dimensions (H/W/T/S) [mm]:</b>	60/415
<b>Light source:</b>	LED	<b>Ingress protection:</b>	IP54
<b>Luminous flux [lm]:</b>	450	<b>Working temperature [°C]:</b>	from -20 to +35
<b>Supply voltage [V]:</b>	220 - 240	<b>Hook:</b>	yes
<b>Frequency [Hz]:</b>	50 - 60	<b>Net weight [kg]:</b>	0.700
<b>Electrical protection class:</b>	II	<b>Warranty [years]:</b>	2
<b>Colour temperature [K]:</b>	4000	<b>ETIM class:</b>	EC000347
<b>Colour rendering index:</b>	>80	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Diffuser material:</b>	PC	<b>Warranty [years]:</b>	2
<b>Diffuser type:</b>	transparent	<b>CE certificate:</b>	<a href="#">258/2023</a>
<b>Material of the body:</b>	gum	<b>Manual:</b>	<a href="#">Download PDF</a>

# PROFI LED 4W PC TRANSPARENT WITH UNIVERSAL PLUG

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
111631	
886584	Magnetic rubber mount



Magnetic rubber mount (886584)

Card creation date: 02 November 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 258/2023