

LINEA S LED 1176MM - 2XEXPO ADJUST 2050LM DALI ZOOM 22-55ST. WHITE 840 20W

KARTA AKCESORIUM



TECHNICAL PARAMETERS

Index:	981296
EAN:	5905963981296
Light source:	COB
Rated power of the luminaire [W]*:	40
Rated power rating 30min [W]:	40
Luminaire rated power 0min [W]:	38.80
Luminous flux [lm]*:	4100
Luminous flux of the luminaire 30min [lm]*:	4100
Supply voltage [V]:	220-240
AC voltage range [V]:	198-264

CHARACTERISTICS

LINEA S LED is a surface-mounted and suspended light line system, representing a new generation of lamps dedicated to LED technology. The innovative connection system and pass-through cabling enables lamps to be quickly combined into a light line and allows flexible replacement of light modules to suit current needs. The design used allows for easy assembly and power connection. The anodised steel body, designed from the ground up, ensures the lamp's strength and robustness, while the narrow side profile allows installation in hard-to-reach areas. Diodes from a renowned manufacturer and new LED modules contribute to the very high luminous efficiency.

APPLICATION

Versatile led lamp designed for indoor use, especially recommended for lighting large-scale commercial, manufacturing and warehouse facilities. The lamp for use in both new applications and replacements of traditional T8 and T5 fixtures with energy-efficient LED solutions.

Card creation date: 20 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr./2023