

TERRANO P 1117MM 5000LM 840 II CL. DALI WHITE 60D (44W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	946226
Ingress protection:	IP20
Luminous flux [lm]*:	5000
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	powder coated steel
Diffuser material:	PC
Diffuser type:	matrix led
Mounting version:	recessed

CHARACTERISTICS

The new linear luminaire in the form of a compact louver with LEDs and focusing lenses allows extremely effective glare reduction (UGR of 12-19). Terrano luminaires are characterised by excellent performance and a number of conveniences. These include, above all, express installation in plasterboard and modular ceilings. The Terrano P lamp - a plastic louver in a slim steel housing - is available in two colour temperatures of 3000 K and 4000 K and in two colour versions: white and black.

APPLICATION

Terrano P is suitable for installation in plasterboard and modular ceilings and is ideal as general lighting, but it can also be used to spotlight selected elements of a space. Terrano P can be used both as an eye-catching feature in modern settings where lighting plays a key role and to complement subtle, minimalist spaces.

TERRANO P 1117MM 5000LM 840 II CL. DALI WHITE 60D (44W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	946226	Optics:	lens
EAN:	5905963946226	Material of the body:	powder coated steel
Light source:	LED module	Colour of the body:	white
Rated power of the luminaire [W]:	44	Ingress protection:	IP20
Supply voltage [V]:	220-240	Mounting version:	recessed
Frequency [Hz]:	50-60	Dimensions (H/W/T/S) [mm]:	1117/40/34
Luminous flux [lm]:	5000	Mounting dimensions [mm]:	1107/33
Luminous efficacy [lm/W]:	114	Dimensions of single box [mm]:	1140/83/44
Energy efficiency class:	E	Number on the palette [pcs]:	506
Electrical protection class:	II	Net weight [kg]:	0.700
Colour temperature [K]:	4000	Category type:	louvres
Colour rendering index:	>80	AC voltage range [V]:	198-264
SDCM:	≤ 3	Light distribution type:	symmetric
Beam angle [°]:	60	DIMM DALI:	yes
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	matrix led	CE certificate:	01/2024
Diffuser colour:	transparent	Manual:	Download PDF
Optics material:	PC		

LIGHT CURVES



Card creation date:13 February 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 01/2024



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl