TERRANO P 1117MM 4600LM 830 II CL. DALI WHITE 60D (36W)

DETAILED CARD





TECHNICAL PARAMETERS

Index: 946363

Ingress protection: IP20

Luminous flux [lm]*: 4600

Color rendering index (Ra) >: 80

SDCM: 3

Energy efficiency class:

Material of the body: powder coated steel

Diffuser material: PC

Diffuser type: matrix led

Mounting version: recessed

CHARACTERISTICS

The new linear luminaire in the form of a compact louver with LEDs and focusing lenses allows extremely effective glare reduction (UGR of 12-19). Terrano luminaires are characterised by excellent performance and a number of conveniences. These include, above all, express installation in plasterboard and modular ceilings. The Terrano P lamp - a plastic louver in a slim steel housing - is available in two colour temperatures of 3000 K and 4000 K and in two colour versions: white and black.

APPLICATION

Terrano P is suitable for installation in plasterboard and modular ceilings and is ideal as general lighting, but it can also be used to spotlight selected elements of a space. Terrano P can be used both as an eye-catching feature in modern settings where lighting plays a key role and to complement subtle, minimalist spaces.



TERRANO P 1117MM 4600LM 830 II CL. DALI WHITE 60D (36W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

| Index: | 946363 |
|-----------------------------------|---------------|
| EAN: | 5905963946363 |
| Light source: | LED module |
| Rated power of the luminaire [W]: | 36 |
| Supply voltage [V]: | 220-240 |
| Frequency [Hz]: | 50-60 |
| Luminous flux [lm]: | 4600 |
| Luminous efficacy [lm/W]: | 128 |
| Energy efficiency class: | Е |
| Electrical protection class: | II |
| Colour temperature [K]: | 3000 |
| Color rendering index (Ra) >: | 80 |
| SDCM: | 3 |
| Power factor: | 0.95 |
| Beam angle [°]: | 60 |
| Diffuser material: | PC |
| Diffuser type: | matrix led |
| Diffuser colour: | transparent |
| Optics material: | PC |
| Optics: | lens |

| Material of the body: | powder coated steel |
|--------------------------------|-------------------------------|
| Colour of the body: | white |
| Ingress protection: | IP20 |
| Mounting version: | recessed |
| Dimensions (H/W/T/S) [mm]: | 1117/40/34 |
| Mounting dimensions [mm]: | 1107/33 |
| Dimensions of single box [mm]: | 1140/83/44 |
| Number on the palette [pcs]: | 506 |
| Net weight [kg]: | 0.700 |
| Category type: | luminaires and linear systems |
| AC voltage range [V]: | 198-264 |
| Light distribution type: | symmetric |
| DIMM DALI: | yes |
| LED lifespan L70B50 [h]: | 150000 |
| LED lifespan L80B20 [h]: | 100000 |
| LED lifespan L90B10 [h]: | 50000 |
| Warranty [years]: | 5 |
| CE certificate: | <u>65/2025</u> |
| Manual: | Download PDF |
| Plik LDT: | Download |

LIGHT CURVES



Card creation date: 02 June 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

