

# CONTRA PLUS LED 595X595MM MULTI 3600-5500LM 840/830 IP20 II CL. PRM PMMA 26-39W DALI

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	374807
<b>Rated power [W] - range:</b>	26-39
<b>Luminous flux of the luminaire [lm] - range:</b>	3600-5500
<b>Colour temperature [K] - range:</b>	4000/3000
<b>Ingress protection:</b>	IP40/IP20
<b>Impact resistance:</b>	IK03
<b>Colour rendering index:</b>	>80
<b>Energy efficiency class:</b>	C
<b>Material of the body:</b>	coated aluminium
<b>Diffuser material:</b>	PMMA

## CHARACTERISTICS

Contra Plus LED versatile LED panel characterised by its low, slim profile and elegant design. Adapted for flush-mounted installation in modular ceilings, surface-mounted or suspended using an additional frame (available as an accessory). Luminaire with integrated energy-saving LED module, made of white painted aluminium profile, equipped with structured multi-layer PMMA MAT or PRM shade for perfect light diffusion.

## APPLICATION

The luminaire is intended for indoor use in office (offices, conference rooms) or representative use (hotels, restaurants); illumination of public facilities, including hospitals, educational facilities, offices, halls, garages, passageways, warehouses, shops, as well as in the food industry and food-related retail and service facilities. The unique design and excellent light performance enable CONTRA PLUS LED to be used as the main source of light, also for work that requires visual focus. The lamp is suitable for both new applications and the replacement of traditional T8 and T5 luminaires with energy-efficient LED solutions.

# CONTRA PLUS LED 595X595MM MULTI 3600-5500LM 840/830 IP20 II CL. PRM PMMA 26-39W DALI

DETAILED CARD

## TECHNICAL PARAMETERS TABLE


Index:	374807	Colour of the body:	white
EAN:	5905963374807	DIMM DALI:	yes
Light source:	LED	Dimensions (H/W/T/S) [mm]:	595/595/39
Rated power [W] - range:	26-39	Impact resistance:	IK03
Luminous flux of the luminaire [lm] - range:	3600-5500	Ingress protection:	IP40/IP20
Colour temperature [K] - range:	4000/3000	Mounting version:	recessed. surface-mounted with accessory, suspended with accessories
Supply voltage [V]:	220-240	Working temperature [°C]:	from 0 to +35
Frequency [Hz]:	50-60	Dimensions of single box [mm]:	636
Luminous efficacy [lm/W]:	138	Number on the palette [pcs]:	50
Energy efficiency class:	C	Net weight [kg]:	1.200
Electrical protection class:	II	Category type:	louvres
Colour rendering index:	>80	LED lifespan L70B50 [h]:	228000
Surge protection [kV]:	1	LED lifespan L80B20 [h]:	143000
Diffuser material:	PMMA	Additional accessories:	surface frame, suspension system
Diffuser type:	PRM	Warranty [years]:	5
Diffuser colour:	transparent	CE certificate:	<a href="#">05/2024</a>
Material of the body:	coated aluminium	Manual:	<a href="#">Download PDF</a>

# CONTRA PLUS LED 595X595MM MULTI 3600-5500LM 840/830 IP20 II CL. PRM PMMA 26-39W DALI

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white
374715	CONTRA LED surface-mounted frame CLICK 600x600x65mm
374708	CONTRA LED surface-mounted frame CLICK 1200x300x65mm
374692	CONTRA LED suspension system 1200x300
374685	CONTRA LED suspension system 600x600
374838	CONTRA LED MOUNTING CLIPS IN KG (4PCS)
374845	Frame adapter KG 635x635 WHITE
374852	Frame adapter KG 1235x335 WHITE



Plasterboard recessing kit 630x630 white (999543)



CONTRA LED suspension system 1200x300 (374692)

Card creation date:12 January 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 05/2024