CORIA 2 10050LM 900MM DALI I CL. IP40 SUSPENDED BLACK MAT 830 105W

DETAILED CARD





TECHNICAL PARAMETERS

Index: 275920

Ingress protection: IP40

Rated power [W] - range: 105

Luminous flux of the luminaire [lm] - $_{10050}$

range:

Colour temperature [K]: 3000

Color rendering index (Ra) >: 80

Electrical protection class:

Material of the body: aluminium

Colour of the body: black

CHARACTERISTICS

The Coria 2 LED circular luminaire with integrated energy-efficient LED module is characterised by its high luminous efficacy and uniform light distribution. Its base is made of white or black powder-coated aluminium and its diffuser is made of microprism (300mm diameter version only) or opal plastic. It is ideal for new applications and for replacing traditional fluorescent lamps with energy-efficient LED solutions. Characteristics: colour temperature 3000K, 4000K; CRI>80; LED module life 119,000 hours (L80B20) ta = 25°C; pendant or surface-mounted version.

APPLICATION

The luminaire is designed for indoor use. It is characterised by even light distribution and good surface illumination, which is why it is particularly dedicated as a source of general light in representative rooms and passageways. Thanks to its excellent luminous parameters, the luminaire is ideal for large conference rooms. The luminaire's construction has been adapted for surface-mounted or flush-mounted installation in plasterboard ceilings. Revit files for architectural luminaires are available on request.



CORIA 2 10050LM 900MM DALI I CL. IP40 SUSPENDED BLACK MAT 830 105W


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	275920
EAN:	5905963275920
Light source:	LED
Rated power [W] - range:	105
Luminous flux of the luminaire [lm] - range:	10050
Luminous efficacy [lm/W]:	96
Energy efficiency class:	Е
Electrical protection class:	1
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Diffuser material:	PC
Diffuser type:	OPAL
Material of the body:	aluminium
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	900/86
Mounting dimensions [mm]:	109/109
Ingress protection:	IP40

Mounting version:	suspended
Working temperature [°C]:	from -10 to +35
DIMM DALI:	yes
	-
Dimensions of single box [mm]:	910
Number on the palette [pcs]:	5
Net weight [kg]:	10.600
Category type:	bulkheads
LED lifespan L70B50 [h]:	189000
LED lifespan L80B20 [h]:	119000
LED lifespan L90B10 [h]:	57000
Light distribution type:	lambertian
SDCM:	3
Warranty [years]:	5
CE certificate:	149/2025
Manual:	Download PDF
Plik LDT:	Download

LIGHT CURVES



Card creation date: 11 January 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

