

# CORIA 2 MULTI 1100-2050LM 400MM DALI RCR I CL. IP44 AW3H BLACK MAT 830 11-22W CORRIDOR

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	274732
<b>Ingress protection:</b>	IP44
<b>Rated power [W] - range:</b>	11-22
<b>Luminous flux of the luminaire [lm] - range:</b>	1100-2050
<b>Colour temperature [K]:</b>	3000
<b>Colour rendering index:</b>	80
<b>Electrical protection class:</b>	I
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	black

## CHARACTERISTICS

The Coria 2 LED circular luminaire with integrated energy-efficient LED module is characterised by its high luminous efficacy and uniform light distribution. Its base is made of white or black powder-coated aluminium and its diffuser is made of microprism (300mm diameter version only) or opal plastic. It is ideal for new applications and for replacing traditional fluorescent lamps with energy-efficient LED solutions. Characteristics: colour temperature 3000K, 4000K; CRI>80; LED module life 119,000 hours (L80B20) ta = 25°C; pendant or surface-mounted version.

## APPLICATION

The luminaire is designed for indoor use. It is characterised by even light distribution and good surface illumination, which is why it is particularly dedicated as a source of general light in representative rooms and passageways. Thanks to its excellent luminous parameters, the luminaire is ideal for large conference rooms. The luminaire's construction has been adapted for surface-mounted or flush-mounted installation in plasterboard ceilings. Revit files for architectural luminaires are available on request.

# CORIA 2 MULTI 1100-2050LM 400MM DALI RCR I CL. IP44 AW3H BLACK MAT 830 11-22W CORRIDOR

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	274732	Working temperature [°C]:	from -10 to +25
EAN:	5905963274732	DIMM DALI:	yes
Light source:	LED	Dimensions of single box [mm]:	430
Rated power [W] - range:	11-22	Number on the palette [pcs]:	24
Luminous flux of the luminaire [lm] - range:	1100-2050	Net weight [kg]:	3
Luminous efficacy [lm/W]:	110	Category type:	bulkheads
Energy efficiency class:	E	LED lifespan L70B50 [h]:	189000
Electrical protection class:	I	LED lifespan L80B20 [h]:	119000
Colour temperature [K]:	3000	LED lifespan L90B10 [h]:	57000
Colour rendering index:	80	Light distribution type:	lambertian
Diffuser material:	PC	SDCM:	≤ 3
Diffuser type:	OPAL	Corridor function:	yes
Material of the body:	aluminium	Motion sensor:	yes
Colour of the body:	black	Emergency lighting [h]:	3
Dimensions (H/W/T/S) [mm]:	400/86	Warranty [years]:	5
Mounting dimensions [mm]:	300	CE certificate:	<a href="#">02/2024</a>
Ingress protection:	IP44	Manual:	<a href="#">Download PDF</a>
Mounting version:	surface		