

CORIA 2 MULTI 1200-2200LM 400MM DALI I CL. IP40 SUSPENDED BLACK MAT 840 11-22W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	274671
Ingress protection:	IP40
Rated power [W] - range:	11-22
Luminous flux of the luminaire [lm] - range:	1200-2200
Colour temperature [K]:	4000
Colour rendering index:	>80
Electrical protection class:	I
Material of the body:	aluminium
Colour of the body:	black

CHARACTERISTICS

The Coria 2 LED circular luminaire with integrated energy-efficient LED module is characterised by its high luminous efficacy and uniform light distribution. Its base is made of white or black powder-coated aluminium and its diffuser is made of microprism (300mm diameter version only) or opal plastic. It is ideal for new applications and for replacing traditional fluorescent lamps with energy-efficient LED solutions. Characteristics: colour temperature 3000K, 4000K; CRI>80; LED module life 119,000 hours (L80B20) ta = 25°C; pendant or surface-mounted version.

APPLICATION

The luminaire is designed for indoor use. It is characterised by even light distribution and good surface illumination, which is why it is particularly dedicated as a source of general light in representative rooms and passageways. Thanks to its excellent luminous parameters, the luminaire is ideal for large conference rooms. The luminaire's construction has been adapted for surface-mounted or flush-mounted installation in plasterboard ceilings. Revit files for architectural luminaires are available on request.

CORIA 2 MULTI 1200-2200LM 400MM DALI I CL. IP40 SUSPENDED BLACK MAT 840 11-22W

DETAILED CARD


TECHNICAL PARAMETERS TABLE

Index:	274671	Ingress protection:	IP40
EAN:	5905963274671	Mounting version:	suspended
Light source:	LED	Working temperature [°C]:	from -10 to +35
Rated power [W] - range:	11-22	DIMM DALI:	yes
Luminous flux of the luminaire [lm] - range:	1200-2200	Dimensions of single box [mm]:	430
Luminous efficacy [lm/W]:	110	Number on the palette [pcs]:	24
Energy efficiency class:	E	Net weight [kg]:	3
Electrical protection class:	I	Category type:	bulkheads
Colour temperature [K]:	4000	LED lifespan L70B50 [h]:	189000
Colour rendering index:	>80	LED lifespan L80B20 [h]:	119000
Diffuser material:	PC	LED lifespan L90B10 [h]:	57000
Diffuser type:	OPAL	Light distribution type:	lambertian
Material of the body:	aluminium	SDCM:	≤ 3
Colour of the body:	black	Warranty [years]:	5
Dimensions (H/W/T/S) [mm]:	400/86	CE certificate:	03/2024
Mounting dimensions [mm]:	109/109	Manual:	Download PDF

Card creation date: 11 January 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 03/2024