


CORIA 2 MULTI 1200-2200LM 400MM DALI I CL. IP44 WHITE MAT 840 11-22W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|-----------|
| Index: | 274626 |
| Ingress protection: | IP44 |
| Rated power [W] - range: | 11-22 |
| Luminous flux of the luminaire [lm] - range: | 1200-2200 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | >80 |
| Electrical protection class: | I |
| Material of the body: | aluminium |
| Colour of the body: | white |

CHARACTERISTICS

The Coria 2 LED circular luminaire with integrated energy-efficient LED module is characterised by its high luminous efficacy and uniform light distribution. Its base is made of white or black powder-coated aluminium and its diffuser is made of microprism (300mm diameter version only) or opal plastic. It is ideal for new applications and for replacing traditional fluorescent lamps with energy-efficient LED solutions. Characteristics: colour temperature 3000K, 4000K; CRI>80; LED module life 119,000 hours (L80B20) ta = 25°C; pendant or surface-mounted version.

APPLICATION

The luminaire is designed for indoor use. It is characterised by even light distribution and good surface illumination, which is why it is particularly dedicated as a source of general light in representative rooms and passageways. Thanks to its excellent luminous parameters, the luminaire is ideal for large conference rooms. The luminaire's construction has been adapted for surface-mounted or flush-mounted installation in plasterboard ceilings. Revit files for architectural luminaires are available on request.

CORIA 2 MULTI 1200-2200LM 400MM DALI I CL. IP44 WHITE MAT 840 11-22W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|---------------|--------------------------------|------------------------------|
| Index: | 274626 | Mounting version: | surface |
| EAN: | 5905963274626 | Working temperature [°C]: | from -10 to +35 |
| Light source: | LED | DIMM DALI: | yes |
| Rated power [W] - range: | 11-22 | Dimensions of single box [mm]: | 430 |
| Luminous flux of the luminaire [lm] - range: | 1200-2200 | Number on the palette [pcs]: | 24 |
| Luminous efficacy [lm/W]: | 110 | Net weight [kg]: | 2.900 |
| Energy efficiency class: | E | Category type: | bulkheads |
| Electrical protection class: | I | LED lifespan L70B50 [h]: | 189000 |
| Colour temperature [K]: | 4000 | LED lifespan L80B20 [h]: | 119000 |
| Colour rendering index: | >80 | LED lifespan L90B10 [h]: | 57000 |
| Diffuser material: | PC | Light distribution type: | lambertian |
| Diffuser type: | OPAL | SDCM: | ≤ 3 |
| Material of the body: | aluminium | Warranty [years]: | 5 |
| Colour of the body: | white | CE certificate: | 02/2024 |
| Dimensions (H/W/T/S) [mm]: | 400/86 | Manual: | Download PDF |
| Mounting dimensions [mm]: | 300 | Plik LDT: | Download |
| Ingress protection: | IP44 | | |