

STRADO LED S 24V 3300LM 740 RM7 IP66 III CL. (20W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	408724
Ingress protection:	IP66
Impact resistance:	IK09
Supply voltage [V]:	DC 24
Rated power of the luminaire [W]*:	20
Luminous flux [lm]*:	3300
Colour temperature [K]:	4000
Colour rendering index:	>70
Electrical protection class:	III
Optics:	RM7

CHARACTERISTICS

STRADO LED 24V uses directional multi-lens arrays, made of PMMA, with each lens having the same optics, ensuring the light characteristics remain constant over time. Components from renowned manufacturers and state-of-the-art LED panels contribute to the very high luminous efficacy achieved at the luminaire's output - reaching 165 lm/W. The upper part of the body has a separate electrical cavity in the body, which allows for efficient cooling of all components, independent of the light module. The lower surface of the luminaire is finished entirely with toughened glass, providing high aesthetic qualities. The luminaire has an outgoing cable, which enables fast, convenient and reliable installation without opening the luminaire. Using standard tools, it is possible to service the luminaire, allowing any component to be replaced without soldering. Body and fixture made of die-cast aluminium, powder-coated grey, IP66 tightness and IK09 mechanical impact resistance. Standard equipment: filter to prevent condensation; outgoing cable for connection to 24V DC power supply. Additional options: choice of optics with different light distribution, choice of different light colour, painting in any RAL colour. Certifications: CE, RoHS.

APPLICATION

The luminaire is suitable for use in low-voltage installations, including customer-supplied photovoltaic and hybrid systems. It is possible to illuminate objects such as: non-public estate roads, roads, squares and internal also private areas, construction site lighting.

STRADO LED S 24V 3300LM 740 RM7 IP66 III CL. (20W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	408724	Exchangeable source:	yes
EAN:	5905963408724	Material of the body:	powder coated aluminium
ETIM class:	EC000062	Colour of the body:	grey
Category type:	street lighting	Dimensions (H/W/T/S) [mm]:	385/265/60
Version:	S	Mounting dimensions [mm]:	ø60
Light source:	LED module	Impact resistance:	IK09
Rated power of the luminaire [W]:	20	Ingress protection:	IP66
Supply voltage [V]:	DC 24	Mounting version:	Top, on pole / Side, on boom
Luminous flux [lm]:	3300	Beam angle adjustment [°]:	-20° to +20°
Luminous efficacy [lm/W]:	165	Lateral surface (SCx) [m2]:	0.018
Energy efficiency class:	B	Working temperature [°C]:	from -40 to +50
Electrical protection class:	III	LED lifespan L90B10 [h]:	100000
Colour temperature [K]:	4000	Control:	Brak
Colour rendering index:	>70	Net weight [kg]:	3.880
SDCM:	≤ 5	Technical Warranty:	5 with the possibility of extension to 10
Diffuser material:	toughened glass	ULOR:	0%
Diffuser type:	transparent	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Optics material:	PMMA	CE certificate:	10/2024
Optics:	RM7	Manual:	Download PDF

LIGHT CURVES



STRADO LED S 24V 3300LM 740 RM7 IP66 III CL. (20W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)



wall holder (galvanized) (314049)



wall holder (grey) (314056)

Card creation date: 16 April 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 10/2024