

# STRADO LED S 24V 6225LM 740 RM7 IP66 III CL. (40W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	408861
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK10
<b>Supply voltage [V]:</b>	DC 24
<b>Rated power of the luminaire [W]*:</b>	40
<b>Luminous flux [lm]*:</b>	6225
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	>70
<b>Electrical protection class:</b>	III
<b>Optics:</b>	RM7

## CHARACTERISTICS

STRADO LED 24V uses directional multi-lens arrays, made of PMMA, with each lens having the same optics, ensuring the light characteristics remain constant over time. Components from renowned manufacturers and state-of-the-art LED panels contribute to the very high luminous efficacy achieved at the luminaire's output - reaching 165 lm/W. The upper part of the body has a separate electrical cavity in the body, which allows for efficient cooling of all components, independent of the light module. The lower surface of the luminaire is finished entirely with toughened glass, providing high aesthetic qualities. The luminaire has an outgoing cable, which enables fast, convenient and reliable installation without opening the luminaire. Using standard tools, it is possible to service the luminaire, allowing any component to be replaced without soldering. Body and fixture made of die-cast aluminium, powder-coated grey, IP66 tightness and IK09 mechanical impact resistance. Standard equipment: filter to prevent condensation; outgoing cable for connection to 24V DC power supply. Additional options: choice of optics with different light distribution, choice of different light colour, painting in any RAL colour. Certifications: CE, RoHS.

## APPLICATION

The luminaire is suitable for use in low-voltage installations, including customer-supplied photovoltaic and hybrid systems. It is possible to illuminate objects such as: non-public estate roads, roads, squares and internal also private areas, construction site lighting.

# STRADO LED S 24V 6225LM 740 RM7 IP66 III CL. (40W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	408861	Material of the body:	powder coated aluminium
Supply voltage [V]:	DC 24	Colour of the body:	grey
EAN:	5905963408861	Dimensions (H/W/T/S) [mm]:	385/265/60
Rated power of the luminaire [W]:	40	Mounting dimensions [mm]:	ø60
Luminous flux [lm]:	6225	Impact resistance:	IK10
Category type:	street lighting	Ingress protection:	IP66
Luminous efficacy [lm/W]:	156	Mounting version:	Top, on pole / Side, on boom
Category of application:	Street lighting	Tilt angle adjustment [°]:	-20° to +20°
Energy efficiency class:	C	Lateral surface (SCx) [m2]:	0.018
Version:	S	Working temperature [°C]:	from -40 to +50
Colour temperature [K]:	4000	Control:	Brak
Light source:	LED module	Net weight [kg]:	3.880
Colour rendering index:	>70	ULOR:	0%
Electrical protection class:	III	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Optics:	RM7	Technical Warranty:	5 with the possibility of extension to 10
SDCM:	≤ 5	CE certificate:	<a href="#">10/2024</a>
Diffuser material:	toughened glass	Environmental Product Declaration (EPD):	<a href="#">682/2024</a>
Diffuser type:	transparent	Manual:	<a href="#">Download PDF</a>
Optics material:	PMMA	LED lifespan L95B10 [h]:	100000

## LIGHT CURVES



# STRADO LED S 24V 6225LM 740 RM7 IP66 III CL. (40W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)



wall holder (galvanized) (314049)



wall holder (grey) (314056)

Card creation date: 16 April 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 10/2024