

# SQ 1200 3000LM PLX RCR I CL. IP20 1192X292MM 830 (29W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	412059
<b>Ingress protection:</b>	IP20
<b>Nominal power [W]:</b>	29
<b>Luminous flux [lm]*:</b>	3000
<b>Colour temperature [K]:</b>	3000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 5
<b>Energy efficiency class:</b>	E
<b>Material of the body:</b>	ABS
<b>Diffuser material:</b>	PS

## CHARACTERISTICS

The SQ 1200 LED is a new line of rectangular raster lights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic for low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Ensures low power consumption and all the advantages of modern LED lamps.

Degree of protection - dependent on mounting method:

- surface-mounted - IP20,
- flush-mounted - IP44/20.

## APPLICATION

Surface-mounted luminaire with the possibility of flush-mounting in modular ceilings and in plasterboard ceilings (using a KG frame/adapter) is particularly recommended for office areas, spacious corridors and public spaces.


# SQ 1200 3000LM PLX RCR I CL. IP20 1192X292MM 830 (29W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	29	Material of the body:	ABS
Index:	412059	Colour of the body:	white
Colour temperature [K]:	3000	Dimensions (H/W/T/S) [mm]:	45/291/1191
EAN:	5905963412059	Mounting dimensions [mm]:	263/1070
Luminous flux [lm]:	3000	Ingress protection:	IP20
Light source:	LED module	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Diffuser type:	OPAL	Motion sensor:	yes
Supply voltage [V]:	220-240	Dimensions of single box [mm]:	55
Frequency [Hz]:	50-60	Number on the palette [pcs]:	50
Luminous efficacy [lm/W]:	100	Net weight [kg]:	1.670
Energy efficiency class:	E	Category type:	louvres
Electrical protection class:	I	LED lifespan L70B50 [h]:	50000
Colour rendering index:	>80	LED lifespan L80B20 [h]:	32000
SDCM:	≤ 5	LED lifespan L90B10 [h]:	15000
Power factor:	0.94	Light distribution type:	open space
Beam angle [°]:	120	Warranty [years]:	5
Diffuser material:	PS	CE certificate:	<a href="#">09/2024</a>
Diffuser colour:	white	Manual:	<a href="#">Download PDF</a>
Optics material:	PMMA		
Optics:	lens		

## LIGHT CURVES



Card creation date: 16 January 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 09/2024



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl