

SQ 1200 3600LM PLX I CL. IP20 1192X292MM 830 (37W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	412073
Ingress protection:	IP20
Nominal power [W]:	37
Luminous flux [lm]*:	3600
Colour temperature [K]:	3000
Colour rendering index:	>80
SDCM:	≤ 5
Energy efficiency class:	E
Material of the body:	ABS
Diffuser material:	PS

CHARACTERISTICS

The SQ 1200 LED is a new line of rectangular raster lights. Designed from the ground up, the design introduces new solutions to ensure excellent light performance. The body is made of plastic for low weight. The diffuser provides the lamp with excellent light characteristics. Integrated LED module Ensures low power consumption and all the advantages of modern LED lamps.

Degree of protection - dependent on mounting method:

- surface-mounted - IP20,
- flush-mounted - IP44/20.

APPLICATION

Surface-mounted luminaire with the possibility of flush-mounting in modular ceilings and in plasterboard ceilings (using a KG frame/adapter) is particularly recommended for office areas, spacious corridors and public spaces.


SQ 1200 3600LM PLX I CL. IP20 1192X292MM 830 (37W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	37	Material of the body:	ABS
Index:	412073	Colour of the body:	white
Colour temperature [K]:	3000	Dimensions (H/W/T/S) [mm]:	45/291/1191
EAN:	5905963412073	Mounting dimensions [mm]:	263/1070
Luminous flux [lm]:	3600	Ingress protection:	IP20
Light source:	LED module	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Diffuser type:	OPAL	Dimensions of single box [mm]:	55
Supply voltage [V]:	220-240	Number on the palette [pcs]:	50
Frequency [Hz]:	50-60	Net weight [kg]:	1.590
Luminous efficacy [lm/W]:	96	Category type:	louvres
Energy efficiency class:	E	LED lifespan L70B50 [h]:	50000
Electrical protection class:	I	LED lifespan L80B20 [h]:	32000
Colour rendering index:	>80	LED lifespan L90B10 [h]:	15000
SDCM:	≤ 5	Light distribution type:	open space
Power factor:	0.95	Warranty [years]:	5
Beam angle [°]:	120	CE certificate:	09/2024
Diffuser material:	PS	Manual:	Download PDF
Diffuser colour:	white		
Optics material:	PMMA		
Optics:	lens		

LIGHT CURVES



Card creation date: 16 January 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 09/2024



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl