

PROXIMA SMD LED 24W BIAŁY AW 3H 4000K

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|------------------------------------|---------|
| Index: | 546020 |
| Ingress protection: | IP65/54 |
| Impact resistance: | IK10 |
| Rated power of the luminaire [W]*: | 29 |
| Luminous flux [lm]*: | 2300 |
| Colour temperature [K]: | 4000 |
| Energy efficiency class: | F |
| Material of the body: | PP |
| Diffuser material: | PC |
| Diffuser type: | OPAL |

CHARACTERISTICS

Surface mounted, round LED light fixture, high ingress protection class IP65 and an integrated energy-saving light source LED GO!. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10). Optional equipment: radio motion sensor (RCR).

APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for outdoor (façade lighting) or indoor use (rooms with high humidity, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms. The luminaire will also work well as a general light source due to the decorative effect that it provides (indirect light distribution on the mounting surface). Two ring colors available: white or silver.

PROXIMA SMD LED 24W BIAŁY AW 3H 4000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|------------------------------|------------------------------|
| Index: | 546020 | Colour of the body: | white |
| EAN: | 5905963546020 | Dimensions (H/W/T/S) [mm]: | ø390/95 |
| Light source: | LED module | Impact resistance: | IK10 |
| Rated power of the luminaire [W]: | 29 | Ingress protection: | IP65/54 |
| Supply voltage [V]: | 220-240 | Mounting version: | surface |
| Frequency [Hz]: | 50 - 60 | Working temperature [°C]: | from 0 to +35 |
| Luminous flux [lm]: | 2300 | Emergency lighting [h]: | 3 |
| Luminous efficacy [lm/W]: | 79 | Number on the palette [pcs]: | 60 |
| Energy efficiency class: | F | Net weight [kg]: | 1.700 |
| Electrical protection class: | I | Category type: | bulkheads |
| Colour temperature [K]: | 4000 | LED lifespan L70B50 [h]: | 110000 |
| Colour rendering index: | >80 | LED lifespan L80B20 [h]: | 72000 |
| Power factor: | 0.90 | LED lifespan L90B10 [h]: | 36000 |
| Beam angle [°]: | 120 | Warranty [years]: | 2 / 0.5 (bateria) |
| Diffuser material: | PC | CE certificate: | 387/2023 |
| Diffuser type: | OPAL | Manual: | Download PDF |
| Material of the body: | PP | | |

LIGHT CURVES

