

# TIUNNE PLUS 200 1600LM 830 60D WHITE IP65/IP20 REFLECTOR B 14W

---

DETAILED CARD



# TIUNNE PLUS 200 1600LM 830 60D WHITE IP65/IP20 REFLECTOR B 14W

## DETAILED CARD

### TECHNICAL PARAMETERS

<b>Index:</b>	921506
<b>Ingress protection:</b>	IP65
<b>Rated power of the luminaire [W]*:</b>	14
<b>Luminous flux [lm]*:</b>	1600
<b>Colour temperature [K]:</b>	3000
<b>Colour rendering index:</b>	80
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	white
<b>Diffuser material:</b>	PC

### CHARACTERISTICS

Tiunne Plus is a decorative downlight luminaire for installation in suspended ceilings. It is energy-efficient and durable thanks to the COB LED light source used. It has a classic circular shape that blends in with any type of space. It is available in several versions with different light distribution angles and four reflector colours.

The lamp housing designed in aluminium ensures optimum working conditions for the LEDs, and the aluminium reflector guarantees high luminous efficiency and low glare - features that distinguish the best LED downlight luminaires. The luminaire is suitable for installation in plasterboard and modular ceilings. Colour temperature 3000K, 4000K; CRI>80, CRI>90.

### APPLICATION

The luminaire is designed for indoor use as general lighting. It is ideal for walkways, entrance areas, shop windows and fitting rooms in commercial premises.

### DETAILS

LED lifespan: L70F50 >60 000h; L80F10 >60 000h; L90F10 57 000h

# TIUNNE PLUS 200 1600LM 830 60D WHITE IP65/IP20 REFLECTOR B 14W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	921506	Optics:	reflector B
EAN:	5905963921506	Material of the body:	aluminium
Light source:	COB	Colour of the body:	white
Rated power of the luminaire [W]:	14	Ring material:	aluminium
Luminous flux [lm]:	1600	Ring colour:	white
Luminous efficacy [lm/W]:	115	Dimensions (H/W/T/S) [mm]:	ø215/110
Energy efficiency class:	D	Mounting dimensions [mm]:	200
Electrical protection class:	II	Ingress protection:	IP65
Colour temperature [K]:	3000	Impact resistance:	IK08
Colour rendering index:	80	Mounting version:	recessed
Beam angle [°]:	60	Category type:	downlights
Surge protection [kV]:	1	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	<a href="#">469/2023</a>
Diffuser type:	transparent	Manual:	<a href="#">Download PDF</a>
Optics material:	aluminium	Plik LDT:	<a href="#">Download</a>

# TIUNNE PLUS 200 1600LM 830 60D WHITE IP65/IP20 REFLECTOR B 14W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
416835	Masking ring 198/257 Tiunne Plus 200 RAL9016
416859	Masking ring 198/257 Square Tiunne Plus 200 RAL9016

Card creation date: 23 October 2024  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 469/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl