

TIUNNE PLUS 200 3500LM 840 DALI 60D WHITE IP65/IP20 REFLECTOR B 36W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	921261
Ingress protection:	IP65
Rated power of the luminaire [W]*:	36
Luminous flux [lm]*:	3500
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	white
Diffuser material:	PC

CHARACTERISTICS

Tiunne Plus is a decorative downlight luminaire for installation in suspended ceilings. It is energy-efficient and durable thanks to the COB LED light source used. It has a classic circular shape that blends in with any type of space. It is available in several versions with different light distribution angles and four reflector colours.

The lamp housing designed in aluminium ensures optimum working conditions for the LEDs, and the aluminium reflector guarantees high luminous efficiency and low glare - features that distinguish the best LED downlight luminaires. The luminaire is suitable for installation in plasterboard and modular ceilings. Colour temperature 3000K, 4000K; CRI>80, CRI>90.

APPLICATION

The luminaire is designed for indoor use as general lighting. It is ideal for walkways, entrance areas, shop windows and fitting rooms in commercial premises.

DETAILS

LED lifespan: L70F50 >60 000h; L80F10 >60 000h; L90F10 57 000h


TIUNNE PLUS 200 3500LM 840 DALI 60D WHITE IP65/IP20 REFLECTOR B 36W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	36	Optics material:	aluminium
Index:	921261	Ring colour:	white
Colour temperature [K]:	4000	Material of the body:	aluminium
EAN:	5905963921261	Dimensions (H/W/T/S) [mm]:	ø215/110
Luminous flux [lm]:	3500	Colour of the body:	white
Light source:	COB	Ring material:	aluminium
Luminous efficacy [lm/W]:	98	Mounting dimensions [mm]:	200
Energy efficiency class:	E	Ingress protection:	IP65
Colour rendering index:	>80	DIMM DALI:	yes
Electrical protection class:	II	Mounting version:	recessed
Beam angle [°]:	60	Category type:	downlights
Surge protection [kV]:	1	CE certificate:	469/2023
Optics:	reflector B	Manual:	Download PDF
Diffuser material:	PC	Plik LDT:	Download
Diffuser type:	transparent		

LIGHT CURVES



TIUNNE PLUS 200 3500LM 840 DALI 60D WHITE IP65/IP20 REFLECTOR B 36W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
416835	Masking ring 198/257 Tiunne Plus 200 RAL9016
416859	Masking ring 198/257 Square Tiunne Plus 200 RAL9016

Card creation date: 23 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 469/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl