

TIUNNE PLUS 200 3800LM 840 DALI 60D WHITE IP65/IP20 REFLECTOR S 36W (TA 50°C)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	913068
Ingress protection:	IP65
Rated power of the luminaire [W]*:	36
Luminous flux [lm]*:	3800
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	E
Material of the body:	aluminium
Colour of the body:	white
Diffuser material:	PC

CHARACTERISTICS

APPLICATION

DETAILS

LED lifespan: L70F50 >60 000h; L80F10 >60 000h; L90F10 57 000h

TIUNNE PLUS 200 3800LM 840 DALI 60D WHITE IP65/IP20 REFLECTOR S 36W (TA 50°C)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	913068	Optics material:	aluminium
EAN:	5905963913068	Optics:	reflector S
Light source:	COB	Material of the body:	aluminium
Rated power of the luminaire [W]:	36	Colour of the body:	white
Luminous flux [lm]:	3800	Ring material:	aluminium
Remarks:	Luminaire luminous flux Ta 50°C: 3300lm	Ring colour:	white
Luminous efficacy [lm/W]:	105	Dimensions (H/W/T/S) [mm]:	ø215/180
Energy efficiency class:	E	Mounting dimensions [mm]:	200
Electrical protection class:	II	Ingress protection:	IP65
Colour temperature [K]:	4000	Mounting version:	recessed
Colour rendering index:	>80	DIMM DALI:	yes
Beam angle [°]:	60	Category type:	downlights
Surge protection [kV]:	1	Version:	special
Diffuser material:	PC	CE certificate:	469/2023
Diffuser type:	transparent	Manual:	Download PDF

Card creation date: 08 August 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 469/2023