

TIUNNE PLUS 200 960LM 840 60D BLACK IP65/IP20 REFLECTOR B 8W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	921278
Ingress protection:	IP65/IP20
Rated power of the luminaire [W]*:	8
Luminous flux [lm]*:	960
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	D
Material of the body:	aluminium
Colour of the body:	white
Diffuser material:	PC

CHARACTERISTICS

Tiunne Plus is a decorative downlight luminaire for installation in suspended ceilings. It is energy-efficient and durable thanks to the COB LED light source used. It has a classic circular shape that blends in with any type of space. It is available in several versions with different light distribution angles and four reflector colours.

The lamp housing designed in aluminium ensures optimum working conditions for the LEDs, and the aluminium reflector guarantees high luminous efficiency and low glare - features that distinguish the best LED downlight luminaires. The luminaire is suitable for installation in plasterboard and modular ceilings. Colour temperature 3000K, 4000K; CRI>80, CRI>90.

APPLICATION

The luminaire is designed for indoor use as general lighting. It is ideal for walkways, entrance areas, shop windows and fitting rooms in commercial premises.

DETAILS

LED lifespan: L70F50 >60 000h; L80F10 >60 000h; L90F10 57 000h


TIUNNE PLUS 200 960LM 840 60D BLACK IP65/IP20 REFLECTOR B 8W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	921278	Optics material:	aluminium
EAN:	5905963921278	Optics:	reflector B
Light source:	COB	Material of the body:	aluminium
Rated power of the luminaire [W]:	8	Colour of the body:	white
Luminous flux [lm]:	960	Ring material:	aluminium
Luminous efficacy [lm/W]:	120	Ring colour:	black
Energy efficiency class:	D	Dimensions (H/W/T/S) [mm]:	ø215/110
Electrical protection class:	II	Mounting dimensions [mm]:	200
Colour temperature [K]:	4000	Ingress protection:	IP65/IP20
Colour rendering index:	>80	Mounting version:	recessed
Beam angle [°]:	60	Category type:	downlights
Surge protection [kV]:	1	CE certificate:	469/2023
Diffuser material:	PC	Manual:	Download PDF
Diffuser type:	transparent		

LIGHT CURVES



Card creation date: 23 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 469/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl