

# PROXIMA SMD LED RCR 24W BIAŁY AW 1H 4000K

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	546129
Ingress protection:	IP65/54
Impact resistance:	IK10
Rated power of the luminaire [W]*:	29
Luminous flux [lm]*:	2300
Colour temperature [K]:	4000
Energy efficiency class:	F
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	OPAL

## CHARACTERISTICS

Surface mounted, round LED light fixture, high ingress protection class IP65 and an integrated energy-saving light source LED GO!. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10). Optional equipment: radio motion sensor (RCR).

## APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for outdoor (façade lighting) or indoor use (rooms with high humidity, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms. The luminaire will also work well as a general light source due to the decorative effect that it provides (indirect light distribution on the mounting surface). Two ring colors available: white or silver.

# PROXIMA SMD LED RCR 24W BIAŁY AW 1H 4000K

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	546129	Colour of the body:	white
EAN:	5905963546129	Dimensions (H/W/T/S) [mm]:	ø390/95
Light source:	LED module	Impact resistance:	IK10
Rated power of the luminaire [W]:	29	Ingress protection:	IP65/54
Supply voltage [V]:	220-240	Mounting version:	surface
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from 0 to +35
Luminous flux [lm]:	2300	Motion sensor:	yes
Luminous efficacy [lm/W]:	79	Emergency lighting [h]:	1
Energy efficiency class:	F	Number on the palette [pcs]:	60
Electrical protection class:	I	Net weight [kg]:	1.700
Colour temperature [K]:	4000	Category type:	bulkheads
Colour rendering index:	>80	LED lifespan L70B50 [h]:	110000
Power factor:	0.90	LED lifespan L80B20 [h]:	72000
Beam angle [°]:	120	LED lifespan L90B10 [h]:	36000
Diffuser material:	PC	Warranty [years]:	2 / 0.5 (bateria)
Diffuser type:	OPAL	CE certificate:	<a href="#">387/2023</a>
Material of the body:	PP	Manual:	<a href="#">Download PDF</a>

## LIGHT CURVES

