

PROXIMA SMD LED RCR 24W DALI (CORR) BIAŁY AW 3H AT 3000K

DETAILED CARD



TECHNICAL PARAMETERS

Index:	546761/PA
Ingress protection:	IP65/54
Impact resistance:	IK10
Nominal power [W]:	24
Luminous flux [lm]*:	2150
Colour temperature [K]:	3000
Energy efficiency class:	F
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Surface mounted, round LED light fixture, high ingress protection class IP65 and an integrated energy-saving light source LED GO!. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10). Optional equipment: radio motion sensor (RCR).

APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for outdoor (façade lighting) or indoor use (rooms with high humidity, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms. The luminaire will also work well as a general light source due to the decorative effect that it provides (indirect light distribution on the mounting surface). Two ring colors available: white or silver.

PROXIMA SMD LED RCR 24W DALI (CORR) BIAŁY AW 3H AT 3000K

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Working temperature [°C]:	from 0 to +35
Nominal power [W]:	24	Corridor function:	yes
Rated power of the luminaire [W]:	29	Motion sensor:	yes
Supply voltage [V]:	220-240	Emergency lighting [h]:	3
Frequency [Hz]:	50 - 60	DIMM DALI:	yes
Luminous flux [lm]:	2150	Net weight [kg]:	1.800
Luminous efficacy [lm/W]:	74	Warranty [years]:	2 / 0.5 (bateria)
Energy efficiency class:	F	CE certificate:	387/2023
Electrical protection class:	I	Index:	546761/PA
Colour temperature [K]:	3000	EAN:	5905963546761/PA
Colour rendering index:	>80	Category type:	bulkheads
Power factor:	0.90	Autotest:	yes
Beam angle [°]:	120	Product line:	standard
Diffuser material:	PC	ETIM class:	EC002892
Diffuser type:	OPAL	LED lifespan L70B50 [h]:	110000
Material of the body:	PP	LED lifespan L80B20 [h]:	72000
Colour of the body:	white	LED lifespan L90B10 [h]:	36000
Dimensions (H/W/T/S) [mm]:	ø390/95	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Impact resistance:	IK10	Warranty [years]:	2 / 0.5 (battery)
Ingress protection:	IP65/54	Manual:	Download PDF
Mounting version:	surface	PZH certificate:	HK/K/0389/01/2017

LIGHT CURVES



Card creation date: 22 January 2019

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 387/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl