
## SQ 300 LED PLUS LENS 2100LM 830 IP54 II KL. AW3H AT OPAL RAL9005 (24W) 300MM

**DETAILED CARD** 





## **TECHNICAL PARAMETERS**

Index:	664304
Ingress protection:	IP54
Impact resistance:	IK08
Nominal power [W]:	24
Luminous flux [lm]*:	2100
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Energy efficiency class:	F
Material of the body:	ABS

## **CHARACTERISTICS**

SQ 300 LED AW is a new line of square ceiling lamps. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, thanks to which it is characterized by low weight and high impact resistance (IK08). The diffuser made of PC polycarbonate provides the lamp with excellent lighting properties. Integrated LED module provides low power consumption and all the advantages of modern lamps with an LED source. The PLUS version of the luminaire line is equipped with brand components from recognized global manufacturers. It is characterized by extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

#### **APPLICATION**

The surface-mounted lamp for ceiling or wall mounting is intended for both indoor use - in rooms with high humidity, passageways, staircases, and outdoor use as façade lighting.



# SQ 300 LED PLUS LENS 2100LM 830 IP54 II KL. AW3H AT OPAL RAL9005 (24W) 300MM


**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

Index:	664304
EAN:	5905963664304
Light source:	LED module
Nominal power [W]:	24
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	2100
Emergency luminous flux [lm]*:	145
Luminous efficacy [lm/W]:	85
Energy efficiency class:	F
Electrical protection class:	II
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Power factor:	0.92
Beam angle [°]:	120
Diffuser material:	PS
Diffuser type:	OPAL
Diffuser colour:	white
Optics material:	PMMA
Optics:	lens
Material of the body:	ABS
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	300/300/58
Mounting dimensions [mm]:	210
Impact resistance:	IK08

Ingress protection:	IP54
Mounting version:	surface
Working temperature [°C]:	from -20 to +35
Emergency lighting [h]:	3
Dimensions of single box [mm]:	305/305/60
Number on the palette [pcs]:	120
Net weight [kg]:	43831
Category type:	dual-function luminaires
Category of application:	educational institutions, HoReCa, commercial facilities
Version:	LENS
Operating mode:	network-emergency
AC voltage range [V]:	220 - 240
LED lifespan L70B50 [h]:	120000
LED lifespan L80B20 [h]:	80000
LED lifespan L90B10 [h]:	40000
Light distribution type:	open space
Photobiological safety:	RG0 - exempt (no photobiological hazard)
Technical Warranty:	2 / 0.5 (battery)
CE certificate:	111/2023
ENEC Certificate:	0316/ENEC/23
PZH certificate:	B-BK-60212-0479/21
CNBOP certificate:	5152/2023
Manual:	Download PDF
Plik LDT:	Download

### **LIGHT CURVES**



Card creation date: 25 November 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

