SQ 300 LED PLUS LENS 2600 LM 840 IP54 II KL. DALI RCR AW3H AT OPAL (25W) 300MM CORRIDOR

DETAILED CARD





TECHNICAL PARAMETERS

Index:	665721
Ingress protection:	IP54
Impact resistance:	IK08
Nominal power [W]:	25
Luminous flux [lm]*:	2600
Colour temperature [K]:	4000
SDCM:	3
Energy efficiency class:	F
Material of the body:	ABS

CHARACTERISTICS

SQ 300 LED AW is a new line of square ceiling lamps. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, thanks to which it is characterized by low weight and high impact resistance (IK08). The diffuser made of PC polycarbonate provides the lamp with excellent lighting properties. Integrated LED module provides low power consumption and all the advantages of modern lamps with an LED source. The PLUS version of the luminaire line is equipped with brand components from recognized global manufacturers. It is characterized by extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

APPLICATION

The surface-mounted lamp for ceiling or wall mounting is intended for both indoor use - in rooms with high humidity, passageways, staircases, and outdoor use as façade lighting.



SQ 300 LED PLUS LENS 2600 LM 840 IP54 II KL. DALI RCR AW3H AT OPAL (25W) 300MM CORRIDOR

DETAILED CARD

TECHNICAL PARAMETERS TABLE


Index:	665721
EAN:	5905963665721
Nominal power [W]:	25
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	2600
Emergency luminous flux [lm]*:	145
Luminous efficacy [lm/W]:	89
Energy efficiency class:	F
Electrical protection class:	II
Colour temperature [K]:	4000
SDCM:	3
Power factor:	0.92
Charging time [h:min]:	48
Battery life [h:min]:	3
Max load (RCR) [W]:	400
Beam angle [°]:	120
Battery:	NiMh
Surge protection [kV]:	1
Diffuser material:	PS
Diffuser type:	OPAL
Diffuser colour:	white
Optics material:	PMMA
Optics:	lens
Material of the body:	ABS
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	300/300/58
Mounting dimensions [mm]:	210
Impact resistance:	IK08

Ingress protection:	IP54
Glow wire test [°C]:	650
Mounting version:	surface
Working temperature [°C]:	from -20 to +35
Corridor function:	yes
Motion sensor:	yes
Emergency lighting [h]:	3
DIMM DALI:	yes
Dimensions of single box [mm]:	305/305/60
Number on the palette [pcs]:	120
Net weight [kg]:	1.220
Category type:	dual-function luminaires
Category of application:	educational institutions, HoReCa, commercial facilities
Version:	LENS
Operating mode:	network-emergency
AC voltage range [V]:	176 - 280
LED lifespan L70B50 [h]:	120000
LED lifespan L80B20 [h]:	80000
LED lifespan L90B10 [h]:	40000
Light distribution type:	open space
Photobiological safety:	RGO - exempt (no photobiological hazard)
Technical Warranty:	2 / 0.5 (battery)
CE certificate:	111/2023
ENEC Certificate:	0316/ENEC/23
PZH certificate:	B-BK-60212-0479/21
CNBOP certificate:	5152/2023
Manual:	Download PDF
Plik LDT:	Download



SQ 300 LED PLUS LENS 2600 LM 840 IP54 II KL. DALI RCR AW3H AT OPAL (25W) 300MM CORRIDOR

DETAILED CARD
LIGHT CURVES



Card creation date: 25 November 2025





This product is a subject to electric and electronic waste equipment regulations (WEEE).