


# SQ 300 LED PLUS LENS 2250 LM 830 IP54 II KL. DALI RCR AW3H AT OPAL RAL9005 (25W) 300MM CORRIDOR

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	665752
Ingress protection:	IP54
Impact resistance:	IK08
Nominal power [W]:	25
Luminous flux [lm]*:	2250
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	F
Material of the body:	ABS

## CHARACTERISTICS

SQ 300 LED AW is a new line of square ceiling lamps. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, thanks to which it is characterized by low weight and high impact resistance (IK08). The diffuser made of PC polycarbonate provides the lamp with excellent lighting properties. Integrated LED module provides low power consumption and all the advantages of modern lamps with an LED source. The PLUS version of the luminaire line is equipped with brand components from recognized global manufacturers. It is characterized by extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

## APPLICATION

The surface-mounted lamp for ceiling or wall mounting is intended for both indoor use - in rooms with high humidity, passageways, staircases, and outdoor use as façade lighting.


# SQ 300 LED PLUS LENS 2250 LM 830 IP54 II KL. DALI RCR AW3H AT OPAL RAL9005 (25W) 300MM CORRIDOR

## DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	665752	Impact resistance:	IK08
EAN:	5905963665752	Ingress protection:	IP54
Nominal power [W]:	25	Glow wire test [°C]:	650
Supply voltage [V]:	220 - 240	Mounting version:	surface
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -20 to +35
Luminous flux [lm]:	2250	Corridor function:	yes
Emergency luminous flux [lm]*:	145	Motion sensor:	yes
Luminous efficacy [lm/W]:	78	Emergency lighting [h]:	3
Energy efficiency class:	F	DIMM DALI:	yes
Electrical protection class:	II	Dimensions of single box [mm]:	305/305/60
Colour temperature [K]:	3000	Number on the palette [pcs]:	120
SDCM:	≤ 3	Net weight [kg]:	1.220
Power factor:	0.92	Category type:	bulkheads
Charging time [h:min]:	48	Category of application:	HoReCa, commercial facilities, educational institutions
Battery life [h:min]:	3	Version:	LENS
Max load (RCR) [W]:	400	AC voltage range [V]:	176 - 280
Beam angle [°]:	120	LED lifespan L70B50 [h]:	120000
Battery:	NiMh	LED lifespan L80B20 [h]:	80000
Surge protection [kV]:	1	LED lifespan L90B10 [h]:	40000
Diffuser material:	PS	Light distribution type:	open space
Diffuser type:	OPAL	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Diffuser colour:	white	Technical Warranty:	2 / 0.5 (battery)
Optics material:	PMMA	CE certificate:	<a href="#">111/2023</a>
Optics:	lens	ENEC Certificate:	<a href="#">0316/ENEC/23</a>
Material of the body:	ABS	PZH certificate:	<a href="#">B-BK-60212-0479/21</a>
Colour of the body:	black	CNBOP certificate:	<a href="#">5152/2023</a>
Dimensions (H/W/T/S) [mm]:	300/300/58	Manual:	<a href="#">Download PDF</a>
Mounting dimensions [mm]:	210		

### LIGHT CURVES



# SQ 300 LED PLUS LENS 2250 LM 830 IP54 II KL. DALI RCR AW3H AT OPAL RAL9005 (25W) 300MM CORRIDOR

DETAILED CARD

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 111/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl