

# SQ 600 LED 4700LM PRM I CL. IP20 592X592MM 840 AW3H (32W) RAL9005

DETAILED CARD



## TECHNICAL PARAMETERS

|   |           |
|---|-----------|
| <b>Index:</b>                           | 669521    |
| <b>Ingress protection:</b>              | IP44/IP20 |
| <b>Nominal power [W]:</b>               | 32        |
| <b>Luminous flux [lm]*:</b>             | 4700      |
| <b>Color rendering index (Ra) &gt;:</b> | 80        |
| <b>SDCM:</b>                            | 3         |
| <b>Energy efficiency class:</b>         | C         |
| <b>Material of the body:</b>            | ABS       |
| <b>Diffuser material:</b>               | PS        |
| <b>Diffuser type:</b>                   | PRM       |

## CHARACTERISTICS

SQ 600 LED AW is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

The luminaire is available in 2 versions:

- with OPAL diffuser - providing soft light;
- with PRM diffuser - with higher luminous efficiency and low glare UGR <19 (18W, 24W, 32W versions).

Available options:

- RCR sensor - sensor used for motion detection, without twilight detection option; uses microwaves for detection (active sensor),
- control in the DALI standard,
- CORRIDOR corridor function (RCR + DALI).

The ingress protection- depends on the method of installation:

- surface mounted - IP20,
- flush-mounted - IP44/20.

## APPLICATION

Surface-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.

# SQ 600 LED 4700LM PRM I CL. IP20 592X592MM 840 AW3H (32W) RAL9005

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|   |               |   |   |
|---|---------------|---|---|
| <b>Index:</b>                           | 669521        | <b>Dimensions (H/W/T/S) [mm]:</b>               | 592/592/44  |
| <b>EAN:</b>                             | 5905963669521 | <b>Mounting dimensions [mm]:</b>                | 563/297   |
| <b>Light source:</b>                    | LED module    | <b>Ingress protection:</b>                      | IP44/IP20   |
| <b>Nominal power [W]:</b>               | 32            | <b>Glow wire test [°C]:</b>                     | 650   |
| <b>Supply voltage [V]:</b>              | 220 - 240V    | <b>Mounting version:</b>                        | surface mounted; recessed mounted in modular ceiling possible |
| <b>Frequency [Hz]:</b>                  | 50 - 60       | <b>Emergency lighting [h]:</b>                  | 3   |
| <b>Luminous flux [lm]:</b>              | 4700          | <b>Net weight [kg]:</b>                         | 2.230   |
| <b>Emergency luminous flux [lm]*:</b>   | 200           | <b>Category type:</b>                           | dual-function luminaires                                      |
| <b>Luminous efficacy [lm/W]:</b>        | 142           | <b>Category of application:</b>                 | educational institutions, commercial facilities               |
| <b>Energy efficiency class:</b>         | C             | <b>AC voltage range [V]:</b>                    | 198 – 264 V   |
| <b>Electrical protection class:</b>     | I             | <b>LED lifespan L70B50 [h]:</b>                 | 132000  |
| <b>Colour temperature [K]:</b>          | 4000          | <b>LED lifespan L80B10 [h]:</b>                 | 84 000  |
| <b>Color rendering index (Ra) &gt;:</b> | 80            | <b>LED lifespan L90B10 [h]:</b>                 | 42000   |
| <b>SDCM:</b>                            | 3             | <b>Light distribution type:</b>                 | open space  |
| <b>Power factor:</b>                    | 0.95          | <b>Operating mode:</b>                          | network-emergency   |
| <b>Charging time [h:min]:</b>           | 3             | <b>Photobiological safety:</b>                  | RG0 - exempt (no photobiological hazard)                      |
| <b>Battery life [h:min]:</b>            | 3             | <b>Technical Warranty:</b>                      | 2 / 0.5 (battery)   |
| <b>Battery:</b>                         | NiMh          | <b>CE certificate:</b>                          | <a href="#">110/2023</a>                                      |
| <b>Battery capacity [mAh]:</b>          | 2100          | <b>PZH certificate:</b>                         | <a href="#">B-BK-60112-0419/2025</a>                          |
| <b>Diffuser material:</b>               | PS            | <b>CNBOP certificate:</b>                       | <a href="#">5152/2023</a>                                     |
| <b>Diffuser type:</b>                   | PRM           | <b>Environmental Product Declaration (EPD):</b> | <a href="#">944/2026</a>                                      |
| <b>Diffuser colour:</b>                 | transparent   | <b>Manual:</b>                                  | <a href="#">Download PDF</a>                                  |
| <b>Material of the body:</b>            | ABS           | <b>ISO Certificates:</b>                        | 9001:2015, 14001:2015, 45001:2018, 50001:2018                 |
| <b>Colour of the body:</b>              | black mat     | <b>Plik LDT:</b>                                | <a href="#">Download</a>                                      |

# SQ 600 LED 4700LM PRM I CL. IP20 592X592MM 840 AW3H (32W) RAL9005

DETAILED CARD

## ACCESSORIES AVAILABLE

| index  | Name   |
|--------|--|
| 999543 | Plasterboard recessing kit 630x630 white (steel version) |
| 978395 | Installation kit SQ 600 Ceiling system H40 100x100       |



Plasterboard recessing kit 630x630 white (steel version) (999543)

Card creation date: 04 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 110/2023