

# SQ 600 LED 8400LM PRM I CL. IP20 592X592MM 840 AW3H (60W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	669620
<b>Ingress protection:</b>	IP44/IP20
<b>Nominal power [W]:</b>	60
<b>Luminous flux [lm]*:</b>	8400
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	ABS
<b>Diffuser material:</b>	PS
<b>Diffuser type:</b>	PRM

## CHARACTERISTICS

SQ 600 LED AW is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

The luminaire is available in 2 versions:

- with OPAL diffuser - providing soft light;
- with PRM diffuser - with higher luminous efficiency and low glare UGR <19 (18W, 24W, 32W versions).

Available options:

- RCR sensor - sensor used for motion detection, without twilight detection option; uses microwaves for detection (active sensor),
- control in the DALI standard,
- CORRIDOR corridor function (RCR + DALI).

The ingress protection- depends on the method of installation:

- surface mounted - IP20,
- flush-mounted - IP44/20.

## APPLICATION

Surface-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.


# SQ 600 LED 8400LM PRM I CL. IP20 592X592MM 840 AW3H (60W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	669620	Material of the body:	ABS
EAN:	5905963669620	Colour of the body:	white
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	592/592/44
Nominal power [W]:	60	Mounting dimensions [mm]:	563/297
Supply voltage [V]:	220 - 240V	Ingress protection:	IP44/IP20
Frequency [Hz]:	50 - 60	Glow wire test [°C]:	650
Luminous flux [lm]:	8400	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Emergency luminous flux [lm]*:	200	Emergency lighting [h]:	3
Luminous efficacy [lm/W]:	129	Net weight [kg]:	2.230
Energy efficiency class:	D	Category type:	louvres
Electrical protection class:	I	Category of application:	commercial facilities, educational institutions
Colour temperature [K]:	4000	LED lifespan L70B50 [h]:	132000
Colour rendering index:	>80	LED lifespan L80B20 [h]:	84 000
SDCM:	≤ 3	LED lifespan L90B10 [h]:	42000
Power factor:	0.95	Light distribution type:	open space
Charging time [h:min]:	3	Technical Warranty:	2 / 0.5 (battery)
Battery life [h:min]:	3	CE certificate:	<a href="#">110/2023</a>
Battery:	NiMh	ENEC Certificate:	<a href="#">PL BBJ/006/2021/M1</a>
Battery capacity [mAh]:	2100	PZH certificate:	<a href="#">B-BK-60212-0618/20</a>
Diffuser material:	PS	CNBOP certificate:	<a href="#">5152/2023</a>
Diffuser type:	PRM	Manual:	<a href="#">Download PDF</a>
Diffuser colour:	transparent		

## LIGHT CURVES




# SQ 600 LED 8400LM PRM I CL. IP20 592X592MM 840 AW3H (60W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white
978395	Installation kit SQ 600 Ceiling system H40 100x100



Plasterboard recessing kit 630x630 white (999543)

Card creation date: 18 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 110/2023