

# SQ 160 LED PLUS P 1900LM 830 IP44/20 II CL. AW3H 75DEG (17W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	572203
Ingress protection:	IP44/IP20
Nominal power [W]:	17
Luminous flux [lm]*:	1900
Colour temperature [K]:	3000
Colour rendering index:	80
Energy efficiency class:	E
Material of the body:	ABS
Colour of the body:	white
Diffuser material:	PC

## CHARACTERISTICS

SQ 160 LED PLUS P AW is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

## APPLICATION

Recessed-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.


# SQ 160 LED PLUS P 1900LM 830 IP44/20 II CL. AW3H 75DEG (17W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	572203	Colour of the body:	white
EAN:	5905963572203	Dimensions (H/W/T/S) [mm]:	158/158/78
Nominal power [W]:	17	Mounting dimensions [mm]:	145/145
Supply voltage [V]:	220 - 240	Impact resistance:	IK08
Frequency [Hz]:	50 - 60	Ingress protection:	IP44/IP20
Luminous flux [lm]:	1900	Mounting version:	recessed
Emergency luminous flux [lm]*:	165	Working temperature [°C]:	od -20 do +35
Luminous efficacy [lm/W]:	101	Emergency lighting [h]:	3
Energy efficiency class:	E	Dimensions of single box [mm]:	310/225/68
Electrical protection class:	I	Number on the palette [pcs]:	180
Colour temperature [K]:	3000	Net weight [kg]:	0.800
Colour rendering index:	80	Category type:	downlights
SDCM:	≤ 3	Operating mode:	M
Power factor:	0.99	UGR (4H8H):	<28
Charging time [h:min]:	24	LED lifespan L70B50 [h]:	132000
Battery life [h:min]:	3	LED lifespan L80B20 [h]:	84000
Beam angle [°]:	75	LED lifespan L90B10 [h]:	42000
Battery:	Ni-Mh	Technical Warranty:	2 / 0.5 (battery)
Battery capacity [mAh]:	2100	CE certificate:	<a href="#">14/2024</a>
Diffuser material:	PC	CNBOP certificate:	<a href="#">5152/2023</a>
Diffuser type:	OPAL	Manual:	<a href="#">Download PDF</a>
Optics:	lens	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Material of the body:	ABS		

## LIGHT CURVES



# SQ 160 LED PLUS P 1900LM 830 IP44/20 II CL. AW3H 75DEG (17W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
998942	Frame square 220 for SQ160 white RAL9016 structure



Frame square 220 for SQ160 white  
RAL9016 structure (998942)

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 14/2024