

# ASTRA LED S 1800LM 840 AR2 IP66 I CL. WIRE 0,7M PLUG/GN SP10KV (13W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	433504
<b>Ingress protection:</b>	IP66
<b>Rated power of the luminaire [W]*:</b>	13
<b>Luminous flux [lm]*:</b>	1800
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	>80
<b>Electrical protection class:</b>	I
<b>Optics:</b>	AR2
<b>Colour of the body:</b>	grey
<b>Luminous efficacy [lm/W]:</b>	138

## CHARACTERISTICS

LED road luminaire with high luminous efficiency and energy-saving integrated LED module. Self-cleaning body made of polypropylene (PP) with fibreglass (FG), handle made of aluminium. The luminaire uses directional lens matrices (made of polycarbonate PC). The luminaire is characterised by a high IP66 ingress protection rating and mechanical impact resistance. The integrated bracket, which is adjustable in increments of 5 degrees, allows adjustment from: -5° to +15° (top, on pole); -5° to +15° (side, on boom). Supplied with 0.7m of H07RN-F cable as standard.

## APPLICATION

Road luminaire suitable for illumination of: streets and municipal, local, internal and neighbourhood roads, cycle paths, alleys, pavements, car parks, squares, private properties and all open spaces.


# ASTRA LED S 1800LM 840 AR2 IP66 I CL. WIRE 0,7M PLUG/GN SP10KV (13W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	433504	Diffuser type:	clear
EAN:	5905963433504	Optics material:	PC
Category type:	street lighting	Optics:	AR2
Light source:	LED module	Material of the body:	PP+15% GF
Rated power of the luminaire [W]:	13	Colour of the body:	grey
Supply voltage [V]:	230	Dimensions (H/W/T/S) [mm]:	75/175/500
Frequency [Hz]:	50	Mounting dimensions [mm]:	fi 64/ fi 78
Luminous flux [lm]:	1800	Ingress protection:	IP66
Luminous efficacy [lm/W]:	138	Mounting version:	Top, on pole / Side, on boom
Energy efficiency class:	C	Lateral surface (SCx) [m2]:	0.016
Electrical protection class:	I	Net weight [kg]:	1.290
Colour temperature [K]:	4000	Wire type:	H07RN-F 3x1.5
Colour rendering index:	>80	Warranty [years]:	5
SDCM:	≤ 4	CE certificate:	<a href="#">16/2024</a>
Power factor:	0.82	Manual:	<a href="#">Download PDF</a>
Surge protection [kV]:	10	ENEC Certificate:	
Diffuser material:	PC		

## LIGHT CURVES



Card creation date: 14 May 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 16/2024



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl