

ASTRA LED S 3350LM 840 AR2 IP66 II CL. WIRE 0,7M PLUG/GN SP10KV 24W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	433566
Ingress protection:	IP66
Rated power of the luminaire [W]*:	25
Luminous flux [lm]*:	3350
Colour temperature [K]:	4000
Colour rendering index:	>80
Electrical protection class:	II
Optics:	AR2
Colour of the body:	grey
Luminous efficacy [lm/W]:	138

CHARACTERISTICS

LED road luminaire with high luminous efficiency and energy-saving integrated LED module. Self-cleaning body made of polypropylene (PP) with fibreglass (FG), handle made of aluminium. The luminaire uses directional lens matrices (made of polycarbonate PC). The luminaire is characterised by a high IP66 ingress protection rating and mechanical impact resistance. The integrated bracket, which is adjustable in increments of 5 degrees, allows adjustment from: -5° to +15° (top, on pole); -5° to +15° (side, on boom). Supplied with 0.7m of H07RN-F cable as standard.

APPLICATION

Road luminaire suitable for illumination of: streets and municipal, local, internal and neighbourhood roads, cycle paths, alleys, pavements, car parks, squares, private properties and all open spaces.


ASTRA LED S 3350LM 840 AR2 IP66 II CL. WIRE 0,7M PLUG/GN SP10KV 24W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	433566	Diffuser type:	clear
Rated power of the luminaire [W]:	25	Optics material:	PC
EAN:	5905963433566	Material of the body:	PP+15% GF
Luminous flux [lm]:	3350	Colour of the body:	grey
Category type:	street lighting	Dimensions (H/W/T/S) [mm]:	75/175/500
Luminous efficacy [lm/W]:	138	Mounting dimensions [mm]:	fi 64/ fi 78
Light source:	LED module	Ingress protection:	IP66
Energy efficiency class:	C	Mounting version:	Top, on pole / Side, on boom
Colour temperature [K]:	4000	Lateral surface (SCx) [m2]:	0.016
Supply voltage [V]:	230	Net weight [kg]:	1.180
Colour rendering index:	>80	Wire type:	H07RN-F 2x1.5
Frequency [Hz]:	50	Warranty [years]:	5
Electrical protection class:	II	CE certificate:	16/2024
Optics:	AR2	Manual:	Download PDF
SDCM:	≤ 4	ENEC Certificate:	
Power factor:	0.94	Plik LDT:	Download
Surge protection [kV]:	10		
Diffuser material:	PC		

LIGHT CURVES



Card creation date: 14 May 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 16/2024