

# ASTRA LED S VD 2000LM 830 AR3 IP66 II CL. WIRE 0,7M PLUG/GN SP10KV 20W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	433825
<b>Ingress protection:</b>	IP66
<b>Rated power of the luminaire [W]*:</b>	20
<b>Luminous flux [lm]*:</b>	2000
<b>Colour temperature [K]:</b>	3000
<b>Colour rendering index:</b>	>80
<b>Electrical protection class:</b>	II
<b>Optics:</b>	AR3
<b>Colour of the body:</b>	grey
<b>Luminous efficacy [lm/W]:</b>	99

## CHARACTERISTICS

LED road luminaire with high luminous efficiency and energy-saving integrated LED module. Self-cleaning body made of polypropylene (PP) with fibreglass (FG), handle made of aluminium. The luminaire uses directional lens matrices (made of polycarbonate PC). The luminaire is characterised by a high IP66 ingress protection rating and mechanical impact resistance. The integrated bracket, which is adjustable in increments of 5 degrees, allows adjustment from: -5° to +15° (top, on pole); -5° to +15° (side, on boom). Supplied with 0.7m of H07RN-F cable as standard.

## APPLICATION

Road luminaire suitable for illumination of: streets and municipal, local, internal and neighbourhood roads, cycle paths, alleys, pavements, car parks, squares, private properties and all open spaces.


# ASTRA LED S VD 2000LM 830 AR3 IP66 II CL. WIRE 0,7M PLUG/GN SP10KV 20W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	433825	Surge protection [kV]:	2
Rated power of the luminaire [W]:	20	Diffuser material:	PC
EAN:	5905963433825	Diffuser type:	clear
Luminous flux [lm]:	2000	Optics material:	PC
Category type:	street lighting	Material of the body:	PP+15% GF
Luminous efficacy [lm/W]:	99	Colour of the body:	grey
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	75/175/500
Energy efficiency class:	E	Mounting dimensions [mm]:	fi 64/ fi 78
Colour temperature [K]:	3000	Ingress protection:	IP66
Supply voltage [V]:	230	Mounting version:	Top, on pole / Side, on boom
Colour rendering index:	>80	Lateral surface (SCx) [m2]:	0.016
Frequency [Hz]:	50	Net weight [kg]:	1.140
Electrical protection class:	II	Wire type:	H07RN-F 2x1.5
Optics:	AR3	Warranty [years]:	3
SDCM:	≤ 3	CE certificate:	<a href="#">17/2024</a>
Power factor:	0.99	Manual:	<a href="#">Download PDF</a>

## LIGHT CURVES



Card creation date: 29 January 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 17/2024



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl