ASTRA LED 2250LM 857 AR4 IP66 II CL. WIRE 0,7M PLUG/GN SP10KV 17W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	433221
Ingress protection:	IP66
Impact resistance:	IK08
Rated power of the luminaire [W]*:	17
Luminous flux [lm]*:	2250
Colour temperature [K]:	5700
SDCM:	5
Color rendering index (Ra) >:	80
Electrical protection class:	II
Energy efficiency class:	D

CHARACTERISTICS

Streetlight LED fitting with high luminous flux (max 153 lm/W) and an integrated energy-saving LED module. The self-cleaning body made of polypropylene (PP) with fibreglass (GF) and the grip made of aluminium. Thanks to the directional lens (made of PC), the light distribution meets the requirements of PN–EN 13201 lighting class. IP66 ingress protection class and IK08 impact-rating features make this fitting extremely tight and shock-resistant (vandal-resistant). Integrated, step-regulated grip allows to set the fitting by 5 degrees in the range of: -5° to +15° (peak to pole); -15° to +5° (side to boom). Options: any RAL color. RCR sensor controlled by remote control.

APPLICATION

Luminaire applicable to: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and mounting: lateral side entry, post-top mounting. Mounting grip integrated with the fitting.

ASTRA LED 2250LM 857 AR4 IP66 II CL. WIRE 0,7M PLUG/GN SP10KV 17W


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	433221
EAN:	5905963433221
Light source:	LED module
Rated power of the luminaire [W]:	17
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Luminous flux [lm]:	2250
Luminous efficacy [lm/W]:	132
Energy efficiency class:	D
Electrical protection class:	II
Colour temperature [K]:	5700
Color rendering index (Ra) >:	80
SDCM:	5
Power factor:	0.90
Diffuser material:	PC
Diffuser type:	matrix led
Diffuser colour:	transparent
Material of the body:	PP+FG
Colour of the body:	gray
Dimensions (H/W/T/S) [mm]:	640/233/113
Mounting dimensions [mm]:	63

Impact resistance:	IK08
Ingress protection:	IP66
Mounting version:	na słupie: szczytowy lub z wysięgnikiem
Working temperature [°C]:	from -20 to +35
Tilt angle adjustment [°]:	od -5 do +15
Lateral surface (SCx) [m2]:	0.170
Wire type:	H07RN-F
Cable length [m]:	0.70
Number on the palette [pcs]:	62
Net weight [kg]:	1.900
Category type:	street lighting
LED lifespan L80B10 [h]:	75000
Light distribution type:	symetryczny/uliczny
Surge protection [kV]:	10
Optics:	AR4
CE certificate:	103/2023
ENEC Certificate:	0324/ENEC/23
Manual:	Download PDF
Category of application:	Street lighting
ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018

LIGHT CURVES




ASTRA LED 2250LM 857 AR4 IP66 II CL. WIRE 0,7M PLUG/GN SP10KV 17W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)
598357	Pole adapter 80/60 ALU
UL00214	Adjustable bracket Astra LED/Astra LED BASIC aluminium grey RAL 9006 diameter 64 mm Corona 2 LED
WSEL431	HAI HD05R RC Programming Remote Control for HD0406VRH IoT



wall holder (galvanized) (314049)




wall holder (grey) (314056)



Pole adapter 80/60 ALU (598357)



Adjustable bracket Astra LED/Astra LED BASIC aluminium grey RAL 9006 diameter 64 mm Corona 2 LED (UL00214)



HAI HD05R RC Programming Remote Control for HD0406VRH IoT (WSEL431)

Card creation date: 02 February 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 103/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl